



Envelope design for low-energy buildings in the tropics: A review

V. Gupta^a, C. Deb^{b,*}

^a Centre for Urban Science and Engineering, IIT Bombay, Mumbai, 400076, Maharashtra, India

^b School of Architecture, Design and Planning, The University of Sydney, Sydney, NSW 2006, Australia

ARTICLE INFO

Keywords:

Building envelope
Building energy performance
Thermal insulation
Energy consumption
Tropics
Building shape

ABSTRACT

The building sector accounts for over one-third of global energy consumption and a significant share of carbon emissions. Improving building energy efficiency, particularly in the tropics, where most of the future development is foreseen, is thus crucial. One of the main factors that determine building energy performance is the building envelope. This paper presents a comprehensive review of the impact of several envelope design variables, such as thermal, optical, physical, and geometrical, on the energy performance of buildings in the tropics.

A correlational analysis that elaborates on the effectiveness of each of these measures is discussed in detail. The findings indicate that insulation, glazing properties, and Window-to-wall ratio (WWR) are promising solutions for improving energy efficiency in tropical buildings. Among these, insulating the building envelope has the most significant impact on energy savings. The variables of building orientation and the thermal mass of building materials have the least influence on total energy consumption. The latter exhibits complex effects in regions characterized by hot-humid climates. An optimized design in cooling-dominated climates should have a large aspect ratio, a higher WWR in the north and south facades, and an ideal shading system. With all variables combined and appropriate ventilation, a building can save 35% of annual energy and up to 60% in some cases. This study further reveals that available research on the effect of building shape and the context of surrounding built environment on energy consumption remains limited.

1. Introduction

According to the United Nations Framework Convention on Climate Change (UNFCCC), addressing building energy efficiency for emission reductions is essential to attaining the goals of the Paris Agreement [1]. COP 26 (2021 United Nations Climate Change Conference) also emphasizes that buildings play a critical role in climate action, stressing the need to reduce emissions by 50% by 2030 and recommending that new buildings be net-zero in terms of operations by 2030 [2]. The recently launched Intergovernmental Panel on Climate Change (IPCC) report also underscores the buildings' potential to achieve Sustainable Development Goals [3].

All of this is in agreement with the assessment that buildings account for more than one-third of global energy demand and more than three-quarters of global greenhouse gas emissions related to energy [1]. Building operations alone are responsible for more than 55% of global electricity [4]. The International Energy Agency (IEA) indicates that if more energy-efficient solutions are not found, the building sector will generate an increased energy demand of 30% by 2060. Substantial

economic and environmental advantages could be realized by improving the sector's energy efficiency.

In the context of rising global average temperatures and growing reliance on electro-mechanical systems for space cooling, the potential for reducing energy demand lies in improving the upcoming building stock in the expanding hot regions [3,5]. Given the region's rapidly emerging building sector, improving building energy efficiency in the tropics is becoming increasingly important.

According to the literature, a variety of variables contribute to the dynamic rise of energy consumption in buildings [6]. The building envelope is critical in determining energy efficiency in buildings [7–9]. It is the shell of the building that acts as a barrier between the conditioned indoor and outside environment. It accounts for 50–60% of heat exchange and can result in 26% of the total building load due to heat gain and 36% of the peak cooling loads in cooling-dominated climates like India [10–12]. The energy performance of different envelope components-walls, floors, roof, ceilings, windows, etc., affects the energy required for building heating and cooling, indoor comfort, ventilation, and natural lighting [13]. Its design variables, such as geometry, insulation, reflectance, thermal mass, shading, etc., affect energy

* Corresponding author.

E-mail addresses: vallary.gupta@iitb.ac.in (V. Gupta), chirag.deb@sydney.edu.au, deb.chirag@iitb.ac.in (C. Deb).

<https://doi.org/10.1016/j.rser.2023.113650>

Received 25 November 2022; Received in revised form 7 August 2023; Accepted 14 August 2023

Available online 24 August 2023

1364-0321/© 2023 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

List of abbreviations:*Acronyms*

ECC	Eta Correlation Coefficient
ECM	Energy Conservation Measures
EMM	Energy Modulation Measures
HVAC	Heating, Ventilation, and Air Conditioning
Low - E	Low Emissivity
OE	Operational Energy
PCM	Phase Change Material
PVR	Passive Volume Ratio
R-value	Thermal Resistance ($\text{m}^2\text{K/W}$)
SC	Shape Coefficient
SP	Shape Proportion
SHGC	Solar Heat Gain Coefficient
UAE	United Arab Emirates
U-value	Thermal Transmittance ($\text{W/m}^2\text{K}$)
W/L	Aspect Ratio or width-to-length ratio
WWR	Window Wall Ratio

Measures

ϵ	Emittance
μ	Reflectance
α	Absorptance
Q	Heat (J)
m	Mass (Kg)
c	Specific Heat Capacity ($\text{J/Kg}\cdot\text{K}$)
C	Thermal Capacity (J/K)
ΔT	Temperature Change (K)
Φ	Heat flow rate (W)
λ	Thermal Conductivity (W/mk)
A	Cross-sectional Area (m^2)
d	Thickness (m)
R	Thermal Resistance ($\text{m}^2\text{K/W}$)
k	Thermal Transmittance ($\text{W/m}^2\text{K}$)
U	Thermal Transmittance of window assembly ($\text{W/m}^2\text{K}$)
R_{se}	External Surface Resistance ($\text{m}^2\text{K/W}$)
τ	Direct Transmittance

performance. Improving these design factors can result in a 46.8% reduction in yearly space-cooling energy consumption in hot climates [14].

Several researchers worldwide have analyzed building envelope variables for improvements in building energy consumption. Thermal and optical properties like thermal capacity, insulation, color, and reflectance can reduce the yearly cooling loads by up to 38% in tropical regions [15–17]. A study for a semi-arid climate reported more than 50% annual energy savings through insulation, reflective paint, low-emissivity (low-E) glazing, and shading [18,19]. Improvements in these measures offer the ability to enhance indoor comfort levels by moderating indoor temperatures [20,21]. Optimizing the building envelope also affects HVAC systems, energy loads, and associated costs [22]. Many review studies assemble optimization of the energy performance of the new or existing buildings. Nonetheless, no comprehensive overview of strategies for enhancing energy efficiency in tropical buildings exists. The following section overviews past studies on building envelope design in the tropics.

1.1. Summary and gaps

1.1.1. Advances in research

A wealth of studies have investigated building energy performance based on several envelope design considerations. The most examined variables include insulation, reflectance, window wall ratio (WWR), glazing types, shading devices, type of walls and roof assembly, ventilation mode, and orientation [14–17,22–32]. While some authors limit their analysis to a few roof or wall, others consider the whole building to produce a more realistic view [33]. The authors have presented methodologies and optimization approaches and highlighted the importance of active and passive design strategies to minimize cooling loads across climatic regions.

In recent times, an increasing body of research has focused on investigating the energy efficiency of buildings situated in tropical regions [17,22,23,31,34–39]. A handful of novel inquiries have sought to evaluate energy efficiency based on building shape [40–43,43–45]. Fig. 1 demonstrates the growing interest in improving the building envelope in the tropics. The trend highlights the rising importance of this issue post-2000. Fig. 2 provides an interesting peak into the type of building envelopes investigated in the tropics. As masonry and concrete remained the most popular envelope types over the years, glazing has received increasing attention over the past decade only, particularly for double-skin facades [39,46–49]. Even within masonry, brick and




Fig. 1. Number of documents published per year.

concrete blocks continue to receive the most attention (79%), followed by stones (4.52%), compressed earth blocks (3.95%), and hollow bricks (3.39%), as illustrated in Fig. 3. It is interesting to note that studies on sustainable envelopes like adobe, timber, and bamboo and conventional systems like semi-transparent photovoltaics have become prevalent in recent years [50–56]. As shown in Fig. 4, more attention has been given to residential buildings (49.2%), followed by offices (28.8%) and educational (11%). However, the literature reviews on building envelope in the tropics are less numerous.

1.1.2. Previous reviews

The reviews to date have ascertained the impact of varying envelope design variables for heating and cooling-dominated climates and captured energy improvements in buildings through the lens of retrofit measures [29,57]. Sarihi et al. reviewed different façade retrofit measures, such as energy conservation measures (ECM) and energy modulation measures (EMM), for minimizing energy demand in both cooling and heating-dominated climates [29]. While ECMs prevent excessive heat transfer through insulation, WWR, and infiltration, EMMs alter energy usage through design strategies like shading, coatings, etc. [29, 58]. Reviews discuss decision-making models for energy performance




Fig. 2. Number of publications in the tropics based on the type of building envelope.




Fig. 3. Distribution of the types of masonry-based envelopes investigated in the tropics. The numerical values on x and y axis are to be used to measure the area of the rectangle for a particular material. The percentage share of each envelope material can consequently be obtained as follows- (area of rectangle/100)
Notes: The labels cement, flyash, gypsum, concrete and tuff in the figure refer to masonry blocks. AAC- Autoclaved Aerated Concrete block; CSEB- Compressed Stabilized Earth Block.

optimization in buildings and software tools for energy simulation [59–61]. Kheiri provided an extensive overview of state-of-the-art methods for optimizing building energy through envelope design [60].

A recent string of review studies underscores the importance of several physical and thermal factors for improving energy efficiency. An exhaustive set of these variables reviewed in cold, warm, and hot climate conditions include building orientation, shape, envelope systems, insulation, heat capacity, and thermal mass [12,33,61–63]. For example, Sadineni et al. covered advancements in fenestration, walls, and roof types for cold regions in the United States and the United Kingdom and hot climates of South Asia and the Middle East [61].

With the growing interest in net zero energy buildings, the design strategies in terms of renewable energy and other technologies and EEMs have also started gaining traction [36]. Feng et al. put together the energy performance in net-zero energy buildings in hot and humid regions [64]. The study found intensive use of passive design technologies for net zero buildings.

Additionally, several other reviews focus on region-specific and contextual climate studies. Friess & Rakhshan focused primarily on United Arab Emirates (UAE) and confirmed the effect of the passive

envelope design on the energy required [65]. Ma & Wang reviewed research on building energy efforts in Hong Kong [66]. It highlights energy-saving measures, including policy, design, and renewable energy systems. The effects of building form and factors like roof and wall type and WWR have also been reviewed for the tropical climate of Malaysia [48]. Other reviews include studies focusing on specific variables. These include shading devices, ventilation strategies, and building insulation materials for varying climate zones [12,20,21,67,68].

The collective findings of these studies offer valuable perspectives on enhancing energy efficiency in buildings through optimizing envelope design parameters across various climatic scenarios or through the proposition of retrofit strategies for pre-existing structures.

1.2. Novelty of the review

A variety of reviews examining building envelope design strategies and variables, along with retrofit measures for minimizing energy use, exist in the literature [21,29,36,59,61,63,67,69–71]. The reviews documented the effect of measures like ECMs, EMMs, passive and active design techniques, natural ventilation, PCM, shading systems,




Fig. 4. Distribution of types of buildings analyzed in the studies conducted in the tropics.

insulation, thermal inertia, facade types, etc., on energy consumption in a particular country (or region) or climate or for different climatic types [20,33,48,58,65,66,70,72]. Some reviews also focus on the climatic design and indoor thermal comfort, however, they do not discuss the effect of envelope design [73,74].

It is to be noted that since the previous reviews, many authors have started investigating the impact of a larger number of envelope design variables on building energy performance in several countries across the tropics [11,18,20,23,47,75–80]. However, prior reviews have not provided a comprehensive and detailed discussion of the studies that investigate the effect of the building envelope in countries across the tropics as a whole. Additionally, no attempt has been made to review the existing literature on the impact of building shape on energy performance.

To enhance our understanding of the tropics, it is imperative to comprehend the historical evolution of trends influencing energy consumption in buildings in these areas. This review paper summarizes and assesses the current body of knowledge that discusses the effect of building envelope on energy consumption in the tropics. It will provide an improved understanding of the variables and building components that are most effective in improving energy performance in such a climate.

The tropics are defined as areas located between the northern latitude of the Tropic of Cancer (about 23°26' North) and the southern latitude of the Tropic of Capricorn (approximately 23°26' South). Its major climatic types as per the Köppen-Geiger classification (Fig. 5) include Tropical rainforest climate (Af), Tropical monsoon climate (Am), Tropical wet and dry or savanna climate (Aw), tropical and subtropical desert climate (BWh, part of BWk) and Mid-latitude steppe and desert climate (BSh) [81]. There are also patches of Type C climate-Humid subtropical climate (Cfa) and Monsoon-influenced humid subtropical climate (Cwa). While type A climate is characterized by a mean monthly temperature of more than 18 °C throughout the year and large amounts of direct solar radiation, type C climate in the tropics exhibits warm and moist conditions with mean daily temperatures ranging from 30 °C to 38 °C. Type B climate shows low precipitation and intense solar radiation [82,83].

The research further suggests that the shape of a building plays a crucial role in determining energy savings. However, this factor has only begun to gain attention in the last decade. With the advent of several capable advanced computational building energy modeling and simulation tools, studies have suggested methodological approaches for determining thermal performance and energy consumption for different building shapes. With this backdrop, the review also proposes collating the state-of-the-art developments on shape in hot and cold climates, representing a further novel contribution of the study.

2. Literature review

A comprehensive literature study was done using three databases-Scopus, Google Scholar, and ScienceDirect without limitation of the year of publication. However, the literature shows that related studies were published majorly between 1998 and 2021. The search was based on the existing studies' title, abstract, and keywords. A combination of the following keywords was used- 'building envelope', 'tropics', 'hot climate', 'thermal performance', 'comfort', 'façade', 'building energy', 'cooling loads', 'shape', 'geometry', 'energy efficiency' and 'energy consumption/demand'. The identified papers were screened based on the relevance of the title, followed by the abstract and area of study or climatic zone. Following this, papers found appropriate for this paper's scope were identified. Additionally, the relevant references mentioned in these papers were also checked based on the criteria mentioned earlier.

Several conditions were applied during the screening process. The studies had to be based in the tropics and assess more than one envelope design variable. The prime objective included building energy performance/demand/consumption or indoor comfort. The search methodology for identifying the relevant literature is demonstrated in Fig. 6.

The content in the following sections is organized as follows. Sections 2.2, 2.3, 2.4, and 2.5 comprehensively review recent studies on different envelope properties and associated design variables. Section 3 summarizes the entire literature and assesses key envelop design variables, followed by the conclusion in section 4.

2.1. Building envelope

The effectiveness of the building envelope is determined by the thermal, physical, and optical characteristics of its components in addition to building geometry [29,41,48]. These properties significantly affect indoor thermal comfort and building energy consumption [58, 84]. Insulation, window properties, and air exchange are critical in cold climates [6]. Optimizing these properties in tropical climates can be difficult due to high daytime temperatures [23,48,85]. Determining their appropriate significance in the tropics influences energy savings [86,87].

The study in the following section summarizes several façade and envelope design variables into four categories, as shown in Fig. 7. Detailed consideration is given to building shape and related metrics. The derived categories include 1) Thermal properties, 2) Optical properties, 3) Physical properties, and 4) Geometry.

2.2. Thermal properties

The building energy loads and temperature of indoor air and envelope surface depend on factors like the outdoor air temperature, solar radiation, and optical and thermal properties of the envelope [88]. Thermal properties are characterized by insulation and thermal mass [18,33,63]. Insulation is determined by the thermal resistance or R-value ($\text{m}^2\text{K/W}$), thermal conductivity (W/mK), and thermal transmittance or U-value ($\text{W/m}^2\text{K}$) [89]. Suitable insulating materials can reduce energy consumption by slowing down the rate of heat flow into building mass by conduction [90]. They exhibit low thermal conductivity compared to commonly used construction materials.

Thermal mass is the total mass of all building elements and affects the energy storage capacity of the material. It depends on thickness, density, and specific heat of wall, roof, and floor [33,90]. There is no significant reduction in the overall thermal gain per day, however, it causes a time lag and a reduction in peak heat flow as a result. High thermal mass helps delay and reduce indoor peak air temperature and reduces the energy consumed in the tropics. The impact is pronounced in a substantial diurnal fluctuation in air temperature [33,61]. It depends on material properties, orientation, and ventilation [91].




Fig. 5. World Map highlighting the different climate types as per Koppen-Geiger climate classification dominant in the Tropics-the areas between the Tropic of Cancer in the Northern Hemisphere and the Tropic of Capricorn in the Southern Hemisphere. The map and color scheme were adopted from Ref. [83].

2.2.1. Thermal transmittance (U-value)

The basic physical mechanisms that facilitate heat transfer in buildings include conduction, convection, and radiation. Fourier's law, or the law of thermal conduction, governs heat transfer by conduction. It states that heat flow rate (Φ) through a solid slab in steady state is always proportional to the cross-sectional area (A) and temperature difference (ΔT) and inversely proportional to the thickness (d) as shown in Eq. (1), where λ is called thermal conductivity. It depends on the slab material and is measured in W/mK [92].

$$\Phi = \lambda \frac{A(\Delta T)}{d} \quad (1)$$

The different layers of materials used in building components like wall, roof etc., are usually characterized by thermal resistance (R). It is the ratio of slab thickness to thermal conductivity as expressed in Eq. (2). It is the inverse of thermal transmittance. Thus, good thermal insulators have low thermal conductivity.

$$R = \frac{d}{\lambda} \quad (2)$$

While the total resistance is the sum of the resistances of the individual material layers ($\sum \frac{d}{\lambda}$), the U-value (k) for such a multilayered body is calculated as per Eq. (3). A low U-value for a material assembly would imply high resistance and thus good thermal insulation.

$$k = \frac{1}{\sum \frac{d}{\lambda}} \quad (3)$$

The application of thermal insulation to reduce the U-value of the building envelope has been studied widely for both hot and cold climates [12,93]. It is the crucial factor impacting the demand for building energy [6,94]. Insulation in tropical regions, such as China, can reduce the annual cooling burden by up to 38% [16,95]. External wall insulation alone can produce considerable energy savings in hot regions [88]. For example, using insulation in Dubai can deliver annual energy savings ranging from 23 to 35% [96].

It appears, however, that using insulation in hot regions has complicated effects [14]. Although insulation can lower the maximum daily daytime temperature by 6 °C, it should be noted that in tropical areas, the indoor air temperature at night may experience a rise of up to 2.8 °C [91,93,97]. Highly insulated and airtight envelopes can increase the overheating risk [9,98–100]. While increasing thickness can be effective in heating-dominated buildings, it does not influence energy loads much in warmer climates [24,25,36]. A low U-value is not inherently associated with low energy consumption in such climates [101–104]. According to a recent study, high U-values in cooling-dominated climates produce more significant operational energy (OE) savings [12].

Meanwhile, in the arid desert climate of UAE, a decrease in U-values can result in a 2.6–19.3% reduction in cooling energy use [105,106]. Similarly, in Indian cities, lower U-values can lead to substantial energy savings of up to 50% [30]. Cooling loads decrease with a lower U-value and vice versa [89]. While increased insulation can curtail heat gain or loss through conduction, it is essential to note that over-insulation¹ may inadvertently result in higher energy consumption [36]. Sen et al. report that higher insulation prevents direct solar gains from radiating back into the atmosphere at night [38]. Nevertheless, natural ventilation can counter the reverse effects of insulation and ensure comfortable nighttime conditions [91].

Such inconsistencies in energy consumption with an increase/decrease in U-value in the tropics are associated with the type of glazing, mode of ventilation, the position of insulation relative to thermal mass, and the local climatic context [19,90]. For instance, combining double glazing with high insulation can cause overheating in the tropics, but the effect is more pronounced in desert and semi-arid climates [98,107].

¹ The thickness of insulation after which any further insulation would be counter-productive, i.e., could result in an overall increase in cooling loads is referred to as the point of thermal inflexion.




Fig. 6. Schematic illustrating the literature search process. The process started with the identification of studies based on the listed criteria, followed by screening and snowballing to shortlist studies appropriate to the scope of this review. The search results presented around 250 papers, forming the basis for the present research work.




Fig. 7. The four major properties of the building envelope and their design variables reviewed in the study.

2.2.1.1. U-values and solar heat gain coefficient (SHGC). Windows considerably affect the thermal performance of the building envelope [108,109]. Heat exchange via glazing depends on properties like U-value, SHGC, and visual transmittance. The negligible thermal resistance offered by the glass and the direct solar radiation affect the total energy a building consumes [7,110]. It is the sum of solar radiation absorbed by the glazing and then re-radiated indoors and the directly transmitted radiation (τ) as shown in Eq. (4), where U is the U-value of window assembly, α is the absorptance of glazing, and R_{se} is the resistance offered by the external glazing surface [92].

$$SHGC = U\alpha R_{se} + \tau \quad (4)$$

The transmitted gains form a significant share of indoor heat gains [111]. A high SHGC can result in overheating even with a low U-value opaque envelope [27]. SHGC² is crucial in reducing cooling energy demand in the tropics [30,58]. Enhancing these characteristics also proves advantageous when considering structures with a high WWR

² It is the fraction of the solar radiation that is absorbed by the building component and then transferred (re-radiated) to the internal environment and the solar radiation that is directly transmitted with respect to total incident solar radiation.

[92]. For a small WWR, however, even a well-insulated envelope can yield energy savings because of reduced solar gains [112].

For example, for a well-insulated envelope with a WWR of 20%, savings reduce as the window U-value changes from 1.95 to 0.68 W/m²K, and SHGC increases from 0.1 to 1.68 [30]. While lowering the U-value for a WWR by more than 50% increases the cooling demand, reducing the SHGC decreases the total energy required by 18.4–29.7% [113]. A reduction in SHGC can also reduce peak indoor temperatures by up to 4.9 °C, reducing the daily cooling load by 34%. The higher the SHGC, the greater the increase in total energy use as a function of WWR for cooling-dominated climates [114]. Poorly insulated buildings, however, may show irregular patterns [113].

Many researchers have also examined the effect of U-value and SHGC under varying climatic conditions and shading types [113]. Friess & Rakhshan suggest a maximum window U-value of 1.9 W/m²K and a shading coefficient of 0.25 in the hot climate of UAE for WWR higher than 60% [65]. SHGC and shading are the most influential factors, with a 39% greater impact than other parameters. When supplemented with Low-E glazing, 10–20% energy savings can be achieved [65].

The literature thus ascertains that SHGC is more effective in decreasing the space cooling demand in well-insulated buildings, irrespective of window size [115]. The effect is, however, more pronounced for larger WWR. Lower U-values prove beneficial for low WWR. It influences heat gains, mainly when solar gains through windows occur during a minor part of the occupied hours [15]. It is worthwhile to point out that a lower SHGC reduces building energy consumption in hot summer regions but increases it in colder regions [116]. Empirical evidence suggests that glazing for hot climates is Low-E, characterized by low values for both SHGC and U-values [52,117]. Table 1 discusses the variations in observed energy savings for different combinations of SHGC and U-value.

2.2.2. Thermal mass

Thermal mass is the ability of a material to absorb and store heat and progressively release it later. In addition to material density, it is ruled by the thermal capacity (C), that depends on mass (or thickness) and specific heat (c), as shown in Eq. (5) [33,90,118]. The amount of heat added (Q) is proportional to the mass of matter (m), specific heat capacity (c), and temperature change (ΔT) as shown in Eq. (6) [92]. The ability to absorb and store heat thus increases with an increase in mass and specific heat.

$$C = m \times c \quad (5)$$

$$Q = mc\Delta T \quad (6)$$

Further, as the thickness increases, the rate of heat flow reduces, resulting in a more significant time lag, as explained by Fourier's law [92]. The greater thickness helps control indoor air temperatures by causing the internal surface temperature to change slowly and with less magnitude [89,90,119]. Most studies report that thermal mass improves indoor thermal comfort for most buildings and climate types [33,99,

120–122]. As per Olsthoorn et al. it is associated with high-temperature cooling or low-temperature heating, implying that cooling/heating time extends over a longer duration [123].

However, it is essential to note that the effects of adding thermal mass are not straightforward. Though it appears to be more pronounced in warm and humid climates, a typical characteristic of the tropics, the literature reveals some discrepancies [124]. For the semi-humid climate of Brazil, high thermal mass can improve indoor thermal comfort and provide savings in cooling energy consumption [125]. The maximum indoor temperature reduces considerably with increased thermal mass [49,126,127]. Similar findings have been reported from studies conducted in Kenya, Cairo, and Israel [128,129]. It can curtail the hours of discomfort caused by overheating by up to 7% in tropical regions like Cairo, Myanmar, and Thailand [99,130]. Reduction in indoor air temperature by up to 4 °C and fluctuations by up to 0.9 °C is possible in hot and dry climates [91,131]. Increasing thermal mass can reduce energy consumption by 13.4% in UAE and peak cooling demand in Hong Kong by up to 60% [105,106].

In contrast, Leccese et al. argue that lighter construction with insulation performs better [132]. Ren and Chen suggest that a lightweight envelope performs better only when the comfort criteria is lowered in tropical regions [133]. According to a study conducted in Thailand, thermally massive walls can reduce air-conditioning loads during the day. It can, however, be counterproductive at night [134]. While the indoor air temperature reduces with rising wall thickness, the mean temperature rises by 1.3 °C during nighttime [91]. Ralegaonkar et al. propose that humid climates with a limited diurnal range should avoid heavy mass construction. Lightweight construction performs better as it can be quickly cooled down [135]. The relatively low time lag reduces indoor nighttime temperature [136]. Similar findings have been reported by studies conducted in regions like Cyprus (Köppen climate classification: BSh), Las Vegas (Köppen climate classification: BWh), Miami, and Phoenix (Köppen climate classification: Aw) that have similar climate characteristics as tropics. Increasing thermal inertia may result in a slight rise in cooling energy demand due to high indoor air temperatures. Authors attribute these observations to night-time ventilation and the use and position of insulation layer [137–139].

In a separate investigation, the researchers suggest that while employing lighter mass may reduce nocturnal cooling, an increase in the thickness of insulation could yield favorable outcomes [31]. Here, the impact of insulation overtakes the effect of thermal mass. However, beyond a certain thickness, the indoor environment remains uninfluenced by the outdoor thermal flux through building mass. Greater thicknesses may thus become less attractive due to less impact and higher costs [91]. High thermal mass can also create overheating when coupled with high insulation [140]. For instance, an increase in the thermal mass of an insulated wall in a sub-tropical climate can lower the demand for heating energy but require more cooling [138].

The inconsistencies are also linked to the level of thermal mass and placement of the insulation layer. The cooling loads can increase by up to 19% or reduce by 16%, depending on the thermal mass and the position of the insulation. Evidence suggests that insulation should be placed on the hotter side to maximize efficiency by minimizing heating of the thermal mass [89,106]. A peak cooling load reduction of 1.8% is possible by moving the layer to outside, irrespective of the thickness [17]. Insulation above the slab can take up to three times longer to transmit the same amount of heat [90]. Several studies confirm that the influence of insulation holds greater significance in tropical areas than thermal mass [33,49,91,120,124,132,137,141,142]. It is important to note that irrespective of the position of thermal mass, shading is crucial to block solar gains in the tropics [99].

The type of climate also influences the effect of thermal mass. For instance, in hot-arid desert climates subjected to high ambient temperatures and intense sunlight, thermal mass stores more heat than it can transfer back outside at night, resulting in discomfort in airtight buildings [138]. For mechanically cooled buildings, internal thermal mass

Table 1
Effect of changing U-value, SHGC, and WWR on energy savings in the tropics as understood from [30,31,113].

WWR	SHGC	Window U-Value	Wall and Roof Insulation	Savings in Cooling Loads
>50% or <50%	Low		High/Low	High
>50% or <50%	High		High/Low	Low
<50%		Low		High
>50%		Low		Low
>50%		High	High	Low
<50%		Low	High	Low/High
>50% or <50%	Irregular	Low	Poor	High

can result in greater energy consumption due to heat transfer from/to the interiors [120]. On the contrary, it can reduce fluctuations in indoor temperatures in hot climate of Jeddah, Saudi Arabia and composite climate of Jaipur, India [127].

Thus, it can be summarized that the effect of thermal mass is complex in the tropics and its application should consider the design of other envelope variables. The discordance can be attributed to factors such as the level of thermal mass, construction material, insulation and its placement, shading, diurnal variations in temperature, climate type, night-time ventilation and air change rate [33,137–139,143,144]. Ventilation and greater air exchanges can increase indoor thermal comfort in the tropical hot-humid climate [143]. Using thermal mass on the interior side with outside insulation appears more beneficial [33].

2.3. Optical properties

The radiant solar energy reaching an external surface is partially reflected and absorbed depending on the surface characteristics. These characteristics can be defined in terms of three optical properties-color, solar absorptance, and emissivity with the effect of the latter two being more prominent [90,145]. Unlike color, which responds to radiation in the visible range, absorptance affects the heating of the surface in both visible and infrared regions. However, the surface's solar absorptance or reflectance is related to the type and color of the external finish [88]. While solar reflectance is the dominant factor affecting thermal performance during the daytime, emissivity is prominent at night [146].

2.3.1. Absorptance or reflection

In accordance with the law of energy conservation, solar radiation falling on an opaque surface can either be absorbed or reflected. As per Eq. (7), the total sum, where μ is the reflectance and α is the absorptance, should be 1.

$$\alpha + \mu = 1 \quad (7)$$

As reflectance increases (μ), absorption (α) reduces. The effectiveness of reflection depends on the color and material texture. Light-colored and smooth surfaces offer greater reflectance or low absorption [136,147]. They serve by reflecting the energetic short waves. The cooling energy requirement increases with the solar absorptance of the external surfaces in hot climates [18,88,148–150]. The annual electricity consumption for a building in China reduced by 8.93%, with a drop in absorptance from 0.6 to 0.2. However, the energy needed for heating increased by 4.02% [151]. A 30% reduction in solar absorption can reduce annual cooling burdens in Singapore by 12.6% [17].

The surfaces with high solar reflectance offer the potential to decrease both surface and indoor air temperatures [152]. Plummeting solar absorptance from 0.65 to 0.1 in Mediterranean climates can reduce indoor air temperature by up to 80% [140]. Reflective paints report up to 7% energy savings [153]. The surface temperatures can drop from 38.9 °C to 9.8 °C with a change in reflectance from 0.1 to 0.9 [145].

2.3.2. Emissivity

As per Kirchhoff's law, the amount of radiation absorbed is equal to the amount emitted, as shown in Eq. (8), where ϵ is the emittance [154]. This is, however, true for the same wavelengths. The wavelength of emitted radiation depends on the temperature of the emitter [90].

$$\epsilon = \alpha \quad (8)$$

High solar reflectance and emissivity can enhance energy efficiency in tropical and subtropical climates [155]. The use of high-emissivity coatings reduces cooling energy consumption by lowering surface temperature. As an example, for a constant value of solar absorptance, the temperature of the external surface at peak can be 39.6 °C for an emissivity of 0.1 and 31.3 °C for an emissivity of 0.9. Koenigsberger et al. state that for two materials with the same solar absorption, the one with higher emissivity will re-emit much of the absorbed heat and attain

a lower temperature [90]. As anticipated, higher emissivity allows heat to escape rapidly [145]. Malz et al. observed a 2.27% reduction in the heat flux through the external wall for a dip in the emissivity from 0.8 to 0.5. A further decrease to about 5.30% was observed as emissivity reduced to 0.2 [1,2].

Certain coatings, like white color, offer high solar reflectance (surface albedo $\geq 65\%$) and thermal emittance [156]. The two properties together make a surface cooler when exposed to solar radiation. The applicability of such cool materials has been extensively investigated, particularly for roofs. As the primary contributor to solar gains in the tropics, cool roofs can significantly reduce cooling burdens and indoor air temperatures [8,93,157]. For instance, Pisello et al. notice that while using a cool roof can reduce the indoor operative temperature by up to 2.6 °C, the application combined with white paint leads to a temperature reduction of 3.1 °C. Covering the whole envelope with a cool coating produces an improvement of 4.4 °C compared to the base case [158].

2.3.2.1. Cool roofs. Cool roofs, also known as white or reflective roofs, are the best-performing technology compared to other passive techniques like roof insulation, green roof, night ventilation, and external shading. While the latter reduces energy consumption by 30%, applying a cool roof alone can save 18–93% in tropical climates [88,150,159,160]. It can reduce the heat flow into the building by 49% and produce greater savings compared to phase change materials (PCM) and green roofs in India [34,161]. One can achieve an annual savings of 10–19% by applying high albedo coating to all uncoated roofs in arid climates [162].

Combining cool roofs with other measures can result in energy savings of up to 78% [163]. Using reflective coatings with PCM can produce savings from 5 to 12% monthly in Singapore [79]. Mousavi et al. however, prefer insulation and reflective paint over PCM, as the former combination is not only thermally effective but results in cost savings too. The coatings can generate more than 50% savings in annual energy consumption in a semi-arid climate [18]. A reflective barrier on an insulated external roof surface can improve its thermal performance by reducing the insulation temperature by up to 4 K during the daytime [164]. Despite its effectiveness in lowering radiation transfer from the outer surface to the insulation layer, this may yield counterproductive results during nighttime due to restricted radiative cooling.

2.3.3. White color coating

The application of color, a strategy used to adapt buildings to the local climate in traditional times, has been identified as an inexpensive approach for reducing summer space cooling demand. As an example, the use of white plaster and clear (cool) paints are capable of reflecting up to 95% of solar radiation and emitting a significant portion of it (infrared emissivity up to 90%) into the surroundings [90,165,166]. While thermally insulated and shaded roofs offer a maximum temperature reduction of 9.9 °C and 8.9 °C respectively, the application of white color can reduce surface temperature by up to 13 °C and indoor air temperatures by 1.2–3.3 °C in hot and arid climates. Applying white paint and glazed tiles can reduce discomfort hours by 100% [149,159,167]. A light-colored roof also results in 30% lesser total heat gain (via conduction and radiation) than a dark-colored roof [168]. An annual reduction of 14–26% in air conditioning is possible by converting dark roofs to white roofs [162]. However, the effect of color on external surfaces reduces with increased insulation. For highly insulated and shaded envelopes, the paint's effect is minor compared to a completely exposed envelope [169].

Overall, the literature determines that exterior surface finishes with light color, high solar reflectance, and emissivity can result in considerable energy savings in the tropics [140]. The measures yield better results when applied on roofs than walls. Increasing reflectance and emissivity can reduce energy consumption in cooling-dominated climates, especially in orientations with significant solar irradiance [153,

170]. Yet, the impact of altering the reflectance and, consequently, its absorption is more significant compared to modifying emissivity [145, 148].

2.4. Physical properties

2.4.1. Opening ratio

The window-to-wall ratio or the opening ratio determines the amount of incident solar radiation that enters indoors. WWR affects the operational carbon from the cooling loads and contributes about 47.4% [26,108]. In cooling-dominated climates, a low WWR is advantageous in façades with a low U-value [29,171]. Higher ratios can produce overheating and, thus, greater cooling energy consumption. Reducing WWR from 1 to 0.4 can reduce indoor air temperature and enhance thermal comfort while ensuring natural ventilation in the tropics, like in China and Malaysia [19,78]. Adjusting window areas can reduce cooling loads by 17.82% in India and 39% in hot and humid regions of the United States [14,172]. A small WWR reduces solar heat gains and enhances comfort levels. However, large windows may be suitable for cooling-dominated climates in the south and north orientation [75,173].

A WWR of 20% in all directions except the south can result in optimum thermal comfort and cooling loads. In the south, a WWR of 60% can provide greater indoor comfort due to the steep angle of incoming solar radiation [42]. For the hot climate of Dubai, Green Building Regulations recommend at least 50% of the glazed areas in the north [65]. It is crucial to determine the appropriate WWR for energy efficiency and thermal comfort and to increase natural ventilation and daylight, particularly in hot and humid climates.

2.4.2. Shading systems

Shading, particularly in external systems, is the most effective measure for blocking solar radiation [23,58]. Different shading typologies can reduce the cooling energy demand in South Africa and Egypt by 25–50% [174,175]. An egg-crate shading device can decrease indoor air temperature and extend indoor comfort hours by 26% in Malaysia's hot-humid climate [23].

Optimal shading achieved by increasing the depth on the east and west façades can reduce cooling burdens by up to 10% in Singapore and Hong Kong [32,151]. The shading of opaque façades in the west and the southwest directions report maximum savings with horizontal and vertical shading types [176].

Heat transfer can also be lessened by installing vertical greenery on external walls. The layers of creeping plants reduce solar radiation by about 40–80% [177,178]. The shading from green façades can reduce indoor temperatures by 8.4 °C in Hong Kong and minimize the external surface temperature of a wall from 18.7 °C to 9.8 °C in Riyadh [29,179]. Analogously, it can substantially reduce roof surface temperatures that otherwise experience high solar irradiation. The daytime average roof temperature in Riyadh can drop by 12.8 °C; Mumbai's greatest maximum reduction is 26.1 °C [179]. The green façades are suitable insulation mechanisms [180,181]. Double-skin green façade on tall structures can reduce cooling energy requirements by 20% and air conditioning loads by 76% in tropical countries like Indonesia, Brazil and Malaysia [39,182–184].

Despite its ability to reduce cooling demands, shading reduces daylight and might be counterproductive during winter due to the reduced solar radiation. It is thus essential to balance WWR, shading, and glazing properties according to the building's orientation [185]. It is worth noting that exterior shading screens should be designed based on the city's solar geometry, building orientation, and climate to provide shading while ensuring daylight ingress and ventilation [27,37]. These may include external movable shading devices or perforated screens that limit solar gains and ensure ventilation and daylighting [24,44]. Findings reveal that such screens can increase the daylight area by 50% and reduce the total transmitted solar radiation by 63%. It can provide 55% savings in annual energy consumption [186].

2.5. Geometry

Apart from the several envelope properties discussed above, other factors contributing to building energy performance include climatic conditions, building shape, and orientation. These factors need to be critically assessed during the building design phase. However, the literature indicates a paucity of studies on building geometry in tropical nations [55,88,131,187]. The following section thus reviews the current literature on building shapes for all climatic zones without limitation to the tropics.

2.5.1. Building shape

Increasing interest in examining the effect of building shape on building energy efficiency is recent. Of the 30-plus shape-centric articles reviewed, 75% have been published in the last decade, as illustrated in Fig. 8.

The building shape impacts the total surface area exposed to the external environment and thus affects the energy losses [188]. A suitable shape and orientation can minimize energy loads by up to 40% without additional costs [189]. The selection of the best-performing shape is linked to variables like compactness index, shape coefficient, and shape proportion [41,63]. Shape proportion (SP) involves changing the proportion of the shape while keeping the volume fixed. Shape coefficient (SC), also called shape factor, refers to the ratio of outer surface area in contact with the exterior surroundings, ground or adjacent non-heated spaces, and internal volume of the building [40,190]. The compactness factor is like the shape coefficient and refers to the ratio of the building volume and its outer surface area [191].

2.5.1.1. Compactness and shape coefficient (SC). Several researchers relate building energy demand with the shape coefficient of buildings. Oral & Yilmaz used SC and other design variables to determine maximum U-values in Turkey [192]. Depecker et al. conceived fourteen parallelepiped buildings for France's cold and mild Mediterranean climate [193]. Observations show that energy consumption is proportional to the SC in a cold climate. In the case of a mild climate with long sunny periods, the heat transmitted via walls is less significant, and thus the correlation with shape is absent. For the tropics, characterized by high solar potential and consequently low transmittance losses, the effect of the increasing SC on the energy demand is low [45].

A very compact building will have a high volume-to-surface ratio, exposing the small building surface to heat transmission. Similar to SC, the compactness index affects a building's capacity to store heat and, consequently, its heat loss [63]. For the hot summers of Athens, more compact shapes (or low SC) resulted in the lowest cooling loads due to lesser surface area. A square-shaped building reported the highest energy performance compared to a rectangular, octagon, or elongated square [42]. Though a low SC is preferred in hot climates, rectangular buildings can also provide significant savings when properly orientated [88]. Studies note that compact buildings are also actively cooled, with indoor air temperatures often below outdoor [194].

Leo Samuel et al. show that dome-shaped roofs in solar-intensive regions like India minimize solar heat gains due to a lower SC and self-shading ability [131]. An inverted U-shape room can further reduce air temperature due to a lesser sun-exposed area [187]. Tang et al. on the contrary, suggest that vaulted roofs result in lower indoor air temperatures due to a larger surface area which permits more heat to be dissipated by convection and thermal radiation at night [55].

Overall, it is seen that a small exposed surface area and a low surface-to-volume ratio (or more compactness) allow buildings to heat up slowly and thus generate reduced energy consumption [194]. The yearly




Fig. 8. Number of papers published on the shape of the building envelope.

energy use for any building form increases as relative compactness³ decreases [114].

2.5.1.2. Indices other than SC and compactness. Ciardiello et al. used shape proportion before calculating SC to adhere to more realistic geometries [41]. They considered eight different building shapes based on the common shapes used in residential buildings. These included linear shape (I), L-shaped (L), court (O) and C-shaped (C) buildings, and some rare shapes like T-shaped (T), H-shaped (H), cross (X) and Y-shaped (Y). After examining four different shape proportions of each shape, the authors identified O, T, H, X, and Y as the best-performing shapes. The findings reveal that optimizing SC and WWR can result in more energy savings. Amraoui et al. suggest that though compact forms reduce cooling loads, a hyper-compact building is undesirable [195]. Literature thus argues that though a low SC assures low energy consumption in cold climates, a direct relation cannot be derived for the tropics. Some researchers recommend using passive volume, the product of the façade's perimeter area (m^2) for every 6 m depth or twice the thermal zone's height, as an efficiency indicator [40]. The compact shapes balanced with high passive volume are preferred for the temperate climate.

The SC or surface area to volume ratio of a building is influenced by its aspect ratio (building width/building length or depth). The building shapes with a higher aspect ratio or W/L correspond to lower values for SC [196]. W/L also impacts the amount of solar radiation hitting any surface. For example, a circular shape with a W/L ratio of 1:1, has the lowest SC and receives the least annual solar radiation. Adamski found buildings with oval shape bases rather than circular and square to offer better thermal performance in heating periods [197]. Research suggests acceptable W/L ratios for hot and humid climates to range between 1.7:1 and 3:1, with 1.7:1 being the optimum shape [75,198].

In addition to conventional building shapes, as discussed above, the performance of free-form building shapes on a building's thermal performance has also been investigated. Determining thermal load characteristics and developing approaches for these shapes has received wide attention. Jin & Jeong used selected physical design and thermal behavior parameters to create different free-form buildings [199]. The authors subsequently demonstrate an optimization process for an energy-efficient design through parametric modeling in Rhinoceros/Grasshopper [43].

Thus, several studies have focused on optimizing building envelopes

to improve energy efficiency through a list of thermal and optical variables but with a narrow focus on optimizing the building shape and surrounding built context [200]. The studies investigating building shapes have been primarily done regarding SC and shape proportion. Appendix A illustrates the building shapes investigated in the reviewed studies.

2.5.1.3. Building orientation. The major factors that govern the association between building shape and incident solar radiation include the W/L ratio and building orientation [196]. Orientation affects insolation and is maximum for geometric shapes with a lower W/L ratio, particularly for east-west elongated shapes [27,196]. Appropriate orientation can limit the heat absorption from surroundings and moderate indoor temperatures [20]. It also impacts the solar reflectance of the external walls, which varies between 0.1 in the south to 0.9 in the east and west [41].

A building oriented north and south results in the slightest heat gain and cooling needs. This is followed by the northwest and the southeast directions, particularly in the tropics [22,90,201]. Longer facades should be made to face the north and south [42]. Changing the building orientation from north/south to east/west can reduce cooling loads between 8.57 and 11.54% for buildings in Singapore [32]. It is seen that the west and southwest-facing orientations perform worst regarding the total number of hours with comfortable indoor air temperatures [202]. Preventing windows in east and west directions can create more acceptable indoor conditions; windows in these directions receive the highest radiation due to a steep angle of incidence [23,203]. A typically solar-controlled north window in a hot-arid climate can provide up to 9% savings in energy consumption. The same can result in 15% savings in the other three directions [30]. The solar gains for different building orientations are illustrated in Fig. 9 [42].

The building orientation also affects the potential for ventilation. Changing orientation to enable natural ventilation can elevate annual indoor thermal hours by 16% in the hot-humid climate of Malaysia [202]. It is wise to orient buildings in a way that permits natural ventilation [166].

The literature thus evidences the importance of orienting the longer building facade in the south or north and the direction of prevailing winds in the tropics. Greater southern exposure limits solar gains due to the nearly vertical angle of incoming solar radiation, preventing sunlight from reaching deep within the floor, as depicted in Fig. 9 [22].

3. Literature summary

According to the literature, the use of studied design variables began in the late 20th century. Building insulation, shading, glazing properties,

³ The relative compactness of a building is defined as the ratio of the volume to the exterior wall area of the building divided by the ratio of a reference building.




Fig. 9. Annual solar gain and cooling loads for different orientations in the Mediterranean climate. E–W means that the building is oriented, with the longer side facing North-South. Reprinted from Ref. [42], with permission from Elsevier.

and reflective coatings have particularly received greater interest. These measures have been majorly used to enhance the thermal properties of the façade by preventing excessive heat transmission. It is seen that using both roof and wall insulation can result in higher savings of up to 35% compared to insulating either of the components. Thermal insulation remains an attractive solution for reducing energy consumption in the tropics. It also dominates the impact of thermal mass.

Several studies also report using low-emissivity coatings for glazing and reflective coatings like cool materials for external surfaces to minimize solar heat gains. In studies published after 2000, variables such as geometry, glazing, SHGC, and thermal mass have been utilized frequently. More research is needed on the effect of shape and adjacent built context on cooling energy consumption, particularly in hot regions. A summary of the energy savings obtained through combinations of different envelope design measures in the tropics is presented in Table 2. If applied in combination, these variables can result in an annual average savings of 35%.

A sensitivity analysis, based on the collated literature, was performed to examine the influence of each envelope design variable on building energy savings. A total of 75 cases that represent a combination of different design variables, as depicted in Table 2, were selected. The analysis was done by examining the Eta coefficient, which measures the strength of association between a scale-dependent variable (maximum energy savings) and the categorical explanatory variables [216]. The Pearson correlation test was then used to determine the significance values (or p-value). The explanatory variables included thermal insulation, shading, WWR, coatings, glazing type, SHGC, and thermal mass. All other variables, like infiltration, ventilation, set point temperatures, etc., were included under the category ‘others’.

The chi-square test of independence was further employed to determine the relationship between each pair of design variables in terms of their investigation in the studied literature. The test compared the frequency of each category for one nominal variable to the second nominal variable. Cramér’s V, an effect size measurement for the chi-square test, was also obtained to measure the strength of association between the design variables [217].

The sensitivity analysis (Table 3) reveals that insulation, glazing type, and WWR have a statistically significant relationship with building energy savings ($p < 0.1$). The insulation has a medium correlation ($ECC > 0.4$) but the largest effect compared to other variables, as shown

in Fig. 10. The type of glazing and WWR are also significant in effecting energy savings in the tropics. The strength of association is however weak ($0.2 < ECC < 0.4$).

This observation is in concurrence with Fig. 11 which discusses the percentage savings produced by the statistically significant variables. As indicated in the figure, the hatched yellow and black lines represent the mean and median, respectively. It illustrates the estimated energy savings possible by using several envelope design measures in the absence or presence of insulation, and by considering modifications in glazing type and WWR in the tropics. The presence of outliers, represented as diamonds, are data points lying significantly outside the range of most observations. These outliers provide insights into the extreme cases of energy savings observed in the literature.

As shown by the yellow line, glazing type, and insulation provide a mean savings of 30% and can save up to 60% when combined with other measures. Without insulation, the average savings are below 20% for a majority of observations. WWR has a considerable impact and can increase average savings by over 10% in combination with other variables. Similar observations have been reported by several studies conducted in the tropics [15,29,101,108,218–220].

The type of glazing can also significantly affect energy savings in the tropics as illustrated in Figs. 10 and 11. Average savings can drop by 10% without appropriate glazing design [15,18,26,30,221,222]. Insulation, however, has a greater maximum savings potential as also observed from sensitivity analysis in Table 3. The use of external insulation can provide substantial savings in energy consumption [34,99,115,117,126,205,223–225]. This alone can yield energy savings of 23–35% [33,93,96,226]. Literature suggests that more savings are observed in hot climates like Oman, Riyadh, Qatar, Delhi, UAE, etc. [16,34,65,93,115,116,183,205]. Roof and wall insulation along with appropriate window-wall ratio can contribute significantly to energy savings in hot climate as also evident from Table 2 [19,69,113,221,227,228].

A moderate correlation ($ECC > 0.4$) between energy savings and others highlights that factors like set-point temperature, ventilation rate, type of HVAC system, etc., also have a comparable effect on energy savings. Literature reports that infiltration, and natural ventilation play a crucial role in hot and humid climate [20,61,77,144,229–231]. Significant energy savings are possible from a relatively higher cooling setpoint temperature across tropical countries [84,232–235]. Thermal mass and orientation were found to be non-significant with the least ECC value ($ECC < 0.2$).

Fig. 12 shows the results from the chi-square test. It demonstrates whether or not a relationship exists between two variables (on the vertical and horizontal axis). A low p-value ($p < 0.1$) indicates that the considered literature provides sufficient evidence to support the existence of a significant relation between a pair of variables, whether they are examined together or not. Findings reveal that in most of the studies conducted in the tropics, the use of insulation has a statistically significant relationship with building orientation ($p < 0.01$). Analogously, a significant chi-square value for glazing with SHGC and WWR ($p < 0.05$), highlighted in black shows that the three envelope variables are also significantly linked (considered/not considered together) in the reviewed literature. A low p-value for shading systems with the external coating ($p < 0.1$) and WWR ($p < 0.05$) also indicates a relationship between the two variables.

The values from the Cramér’s V test, as shown in Fig. 13, illustrate the strength of association between a pair of variables on the two axes. For instance, Cramér’s V value of 0.3 between WWR and shading indicates a strong positive association between the two variables. A large V value along with a low p-value suggests that the two variables are often examined together to evaluate building energy performance in the tropics [14,19,28,75,78,117,208–210,236]. However, the figure also suggests that though insulation and building orientation are statistically related ($p < 0.09$), the variables are weakly associated (Cramér’s V = 0.2). Studies that examine insulation rarely consider the effect of

Table 2

A summary of the annual savings (%) obtained by applying combinations of different envelope design solutions. The studies are arranged in descending order of their resulting energy savings [206,207,211,212,214].

Source	Insulation	Exterior coating or color	Glazing Type	Shading	WWR	SHGC	Orientation	Thermal mass	Others	Maximum savings in annual energy consumption (%)
[206]										86
[98]										66
[183]										57.7
[207]										53
[28]										50
[117]										47.3
[14]										46.81
[208]										42.34
[209]										39.5
[15]										38
[207]										35.6
[117]										35
[18]										34
[175]										33
[18]										32
[17]										31.4
[207]										31.2
[207]										30
[210]										28
[207]										27
[175]										26.7
[211]										26.35
[212]										25.92
[93]										25.4
[145]										25
[18]										25
[194]										24
[18]										22
[30]										22
[209]										22
[213]										21.3
[214]										21
[215]										20.5
[209]										20.4
[14]										20.26
[17]										19.4
[194]										19
[117]										18

changing building orientation as demonstrated in Table 2 [12,18,49,70,91,95,120,124,132,140,175,204,213,215,237,238].

The results show that type of glazing has a moderate level of association with SHGC and WWR. For instance, almost all studies that examine SHGC, consider the effect of the kinds of glazing [18,75,93,110,112,117,204,239]. The same holds for studies examining glazing type and WWR as also shown in Table 2. However, comparatively more research has been conducted on the combined effects of glazing type and WWR than on SHGC and WWR in the tropics [19,26,28,65,97,185,208,

209,232,240–245]. Notably, glazing, WWR, and insulation all contribute substantially to energy savings, as discussed in Figs. 10 and 11. It is evident from Fig. 12 and Table 2 that insulation with glazing type and insulation with other variables have received equal attention [26,29,31,36,95,102,120,144,219,221,238,242,246].

Despite a significant relationship of shading with coating and WWR as discussed in Fig. 12, the latter has a stronger association. This suggests a growing interest in examining the impact of shading and WWR on building energy performance in tropical regions [14,19,117,175,




Table 3
Comparison of the importance of studied envelope variables.

Variables	Eta correlation coefficient (ECC)
Insulation	0.419***
Shading	0.204
Coating	0.271
Glazing type	0.314**
WWR	0.244*
SHGC	0.220
Orientation	0.162
Thermal mass	0.047
Others	0.430***

*p < 0.10, **p < 0.05, ***p < 0.01.

208–210,242,247,248]. It is evident from Table 2 that only a limited number of studies have assessed shading and coating together [14,17].

Attempts have also been made to examine shading, glazing, and WWR simultaneously [19,242,244,247]. Almost all studies that evaluate the impact of WWR also consider shading and glazing. An insignificant relation between insulation and thermal mass indicates a paucity of

literature assessing the combined effect of these variables on energy savings in the tropics. Most existing studies examine their impact on indoor thermal comfort [91,128,129,131,249,250].

4. Conclusion

Buildings account for a considerable share of total energy consumption for space cooling, specifically in tropical regions. Thus, the relationship between building envelope design and energy consumption has received growing attention in recent years. The present review provides a comprehensive discussion of the studies that investigate the effect of several envelope design variables in countries across the tropics as a whole. It summarizes their impact on building energy consumption and thermal performance. The reviewed literature confirms that energy consumption can be reduced by making cautious modifications to the thermal, physical, and optical design variables of the building envelope and its geometry.

Building envelope design variables such as insulation or U-value, glazing properties, and WWR have primarily been recognized as promising solutions for improving energy efficiency in tropical buildings. The




Fig. 10. The importance of building envelope variables for savings in annual energy consumption.




Fig. 11. Annual savings in energy consumption with/without the use of insulation, WWR, and glazing type.




Fig. 12. The statistical significance of association between pairs of building design variables-p-value (2-tailed sig.) for the chi-square test. A low p-value ($p < 0.1$) indicates a significant relationship. use of thermal mass and orientation have a minimal influence on total energy consumption. An optimized design in hot climates should have a large aspect ratio, higher WWR in the north and south, and an ideal




Fig. 13. Comparing the strength of association between pairs of building design variables- Cramér's V for the chi-square test. A large value indicates a stronger relationship. shading system with low-E coating glazing. External shading in the form of green vegetation or perforated screens designed per the city's solar geometry can be effective in cooling-dominated climates. Increasing

reflectance and emissivity can reduce energy consumption, especially in orientations with significant solar irradiance. Factors like set-point temperature, ventilation rate, type of HVAC system, etc., also have a substantial effect on energy savings in hot and humid climates. While some variables have a direct link with savings, others are found to be more complicated in the tropics.

In general, there is the potential to save 35% of building energy annually and up to 60% when all variables are taken into account. The annual average can, however, fall below 20% without insulation. Roof and wall insulation along with an appropriate window-wall ratio can contribute significantly to energy savings in hot climate. It is important to note that insulation does not offer similar benefits for all configurations. While it can be effective for a low WWR and glazing with a low SHGC, it can be detrimental for large WWR in the west and east. Insulation should be applied considering factors like WWR, thermal mass, and glazing properties. While these variables effectively reduce conductive and convective heat gains, SHGC helps control direct heat transmission. However, fewer studies have been conducted on the combined effects of glazing type, WWR, and SHGC in the tropical countries.

The literature reports contradictions when considering thermal mass in hot-humid climates. The impacts of adding thermal mass are not straightforward in hot-humid climates. While thermally massive walls can reduce indoor air temperature during the day, they can be counterproductive at night. Additionally, it can result in greater energy consumption in hot-arid climate. The discrepancy can be attributed to factors like construction material, level of insulation, diurnal variations in temperature, outdoor climate type, night-time ventilation etc. In order to account for the variations, the use of thermal mass in the tropics should employ tools that capture its dynamic behavior. The studies should consider the holistic effect of other design variables and varying micro-climate. Interventions should be adapted to local climate and characteristics of the building.

Many existing studies have examined the effect of thermal, optical and physical properties of building envelope components on energy use and thermal comfort in tropical countries. However, there is a disconnect between the studies examining the combined effect of envelope

variables and factors like occupants, equipment and appliances, HVAC systems etc. There needs to be more literature trying to assess the combined effects of envelope design properties along with variations in occupancy pattern, ventilation type, equipment schedule and efficiency, setpoint temperatures, etc. Furthermore, although precise information on such characteristics might potentially reveal causative links and a common platform for a more logical comparison, such details are often lacking in the available research.

Further examination shows that building shape can significantly affect thermal comfort by impacting solar gains in the hot-humid climate. Lately, few attempts have been made to determine the thermal characteristics of free-form structures. However, there is limited research on the effect of changing building shape on energy consumption, particularly in the tropics. Additionally, more research is needed to investigate the combined impact of envelope design variables and urban form on indoor thermal comfort and energy consumption in the tropics.

Lastly, further research is required to investigate the link between envelope design, occupant behavior, urban form and appliance activity use in the context of potential for renewable energy, target users, and accessibility. A more comprehensive understanding is vital to identify critical parameters required to enhance energy efficiency in buildings and address issues related to sustainable development.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Data availability


Data will be made available on request.

Acknowledgments

The authors would like to thank the journals that permitted the use of Figs. 5 and 9, and other Figures used in Appendix A.





Appendix A

Building shapes and façade types investigated in cited literature work. Reprinted from Refs. [40,41,43,45,114], with permission from Elsevier.

Source	The figure of scheme/case study	Elements and techniques established in literature
[41]	 <p>SP1 SP2 SP3 SP4</p> <p>L1 SC=0.44m⁻¹ L2 SC=0.38m⁻¹ L3 SC=0.33m⁻¹ L4 SC=0.34m⁻¹</p> <p>L1 SC=0.44m⁻¹ L2 SC=0.38m⁻¹ L3 SC=0.32m⁻¹ L4 SC=0.34m⁻¹</p> <p>O1 SC=0.42m⁻¹ O2 SC=0.42m⁻¹ O3 SC=0.37m⁻¹ O4 SC=0.33m⁻¹</p>	<p>Shape I- shape proportions (SP) and corresponding shape coefficients (SC)</p> <p>Shape L- SC for SP 1, SP 2, SP 3, SP 4 respectively</p> <p>Shape O- SC for SP 1, SP 2, SP 3, SP 4 respectively</p>










(continued on next page)

(continued)

Source	The figure of scheme/case study	Elements and techniques established in literature
		<p>Shape C– SC for SP 1, SP 2, SP 3, SP 4 respectively</p> <p>Shape T– SC for SP 1, SP 2, SP 3, SP 4 respectively</p> <p>Shape H– SC for SP 1, SP 2, SP 3, SP 4 respectively</p> <p>Shape X–SC for SP 1, SP 2, SP 3, SP 4 respectively</p> <p>Shape Y– SC for SP 1, SP 2, SP 3, SP 4 respectively</p>
[43]		<p>Free-form building type</p>
[114]		<p>Buildings with relative compactness = 0.689</p> <p>Buildings with relative compactness = 0.158</p>
[45]		<p>Building geometry with SC = 1.472</p> <p>Building geometry with SC = 1.476</p>

(continued on next page)

(continued)

Source	The figure of scheme/case study	Elements and techniques established in literature
	<p>Model 3</p> 	Building geometry with SC = 1.503
	<p>Model 4</p> 	Building geometry with SC = 1.553
	<p>Model 5</p> 	Building geometry with SC = 1.578
	<p>Model 6</p> 	Building geometry with SC = 1.589
	<p>Model 7</p> 	Building geometry with SC = 1.656
[40]	 <p>Alt. 1 Alt. 3 Alt. 12</p>	Passive Volume Ratio (PVR) for Alt 1 = 0.77 Alt 3 = 0.83 Alt 12 = 0.87
	 <p>Alt. 2 Alt. 7 Alt. 8</p>	PVR for Alt 2 = 0.85 Alt 7 = 0.79 Alt 8 = 0.82
	 <p>Alt. 5 Alt. 7 Alt. 15</p>	PVR for Alt 5 = 0.85 Alt 7 = 0.90 Alt 15 = 0.89
	 <p>Alt. 2 Alt. 6 Alt. 11</p>	PVR for Alt 5 = 0.87 Alt 7 = 0.83 Alt 15 = 0.90

References

- [1] UNEP, IEA, UCL. Global status report for buildings and construction | Globalabc 2021. 2020. <https://globalabc.org/resources/publications/2021-global-status-report-buildings-and-construction>. [Accessed 27 March 2022].
- [2] Jones H. BuildingToCOP26 Coalition accelerates climate action ahead of cities, regions and built environment day at COP26. World Green Build Counc; 2021. <https://www.worldgbc.org/news-media/buildingtocop26-coalition-accelerates-climate-action-ahead-cities-regions-and-built>. [Accessed 26 March 2022].
- [3] IPCC. Climate change 2022: Mitigation of climate change 2022. Working Group III Contribution to the Sixth Assessment Report of the Intergovernmental Panel on Climate Change; 2022. <https://www.ipcc.ch/report/ar6/wg3/>. [Accessed 10 April 2022].
- [4] IEA, UNEP. Global status report for buildings and construction: towards a zero-emission 2020. 2020. https://globalabc.org/sites/default/files/inline-files/2020%20Buildings%20GSR_FULL%20REPORT.pdf. [Accessed 20 June 2022].
- [5] IEA. The Future of Cooling – Analysis. IEA 2018. <https://www.iea.org/reports/the-future-of-cooling> (accessed March 27, 2022)..
- [6] Levine M, Ürge-Vorsatz D, Blok K, Geng L, Harvey D, Lang S, et al. Residential and commercial buildings. In: Climate change 2007: mitigation. Contribution of working group III to the fourth assessment report of the Intergovernmental Panel on Climate Change; 2007.
- [7] Leskovar VZ, Premrov M. An approach in architectural design of energy-efficient timber buildings with a focus on the optimal glazing size in the south-oriented façade. Energy Build 2011;43:3410–8. <https://doi.org/10.1016/j.enbuild.2011.09.003>.
- [8] Shohan AAA, Al-Khatiri H, Bindajam AA, Gadi MB. Solar gain influence on the thermal and energy performance of existing mosque buildings in the hot-arid climate of Riyadh city. Sustainability 2021;13:3332. <https://doi.org/10.3390/su13063332>.
- [9] Zhao M, Künzel HM, Antretter F. Parameters influencing the energy performance of residential buildings in different Chinese climate zones. Energy Build 2015;96: 64–75. <https://doi.org/10.1016/j.enbuild.2015.03.007>.
- [10] Bano F, Kamal MA. Examining the Role of building envelope for energy efficiency in office buildings in India. Architect Res 2016;2016. <https://doi.org/10.5923/j.arch.20160605.01>. 107–15.
- [11] Haase M, Amato A. Sustainable façade design for zero energy buildings in the tropics. 2006. p. 6. Geneva, Switzerland.
- [12] Kumar D, Alam M, Zou PXW, Sanjayam JG, Memon RA. Comparative analysis of building insulation material properties and performance. Renew Sustain Energy Rev 2020;131:110038. <https://doi.org/10.1016/j.rser.2020.110038>.
- [13] IEA. Technology. Roadmap energy efficient building envelopes, vol. 68; 2013.
- [14] Sang X, Pan W, Kumaraswamy MM. Informing energy-efficient building envelope design decisions for Hong Kong. Energy Proc 2014;62. <https://doi.org/10.1016/j.egypro.2014.12.373>.
- [15] Bojic M, Yik FWH, Sat P. Energy performance of windows in high-rise residential buildings in Hong Kong. Energy Build - ENERGBLDG 2002;34:71–82. [https://doi.org/10.1016/S0378-7788\(01\)00079-2](https://doi.org/10.1016/S0378-7788(01)00079-2).
- [16] Bojic M, Yik F. Cooling energy evaluation for high-rise residential buildings in Hong Kong. Energy Build 2005;37:345–51. <https://doi.org/10.1016/j.enbuild.2004.07.003>.
- [17] Cheung C, Fuller RJ, Luther M. Energy-efficient envelope design for high-rise apartments. Energy Build 2005;37:37–48. <https://doi.org/10.1016/j.enbuild.2004.05.002>.
- [18] Mousavi N, Gijón-Rivera M, Solorio C, Rangel C. Energy, comfort, and environmental assessment of passive techniques integrated into low-energy residential buildings in semi-arid climate. Energy Build 2022;112053. <https://doi.org/10.1016/j.enbuild.2022.112053>.
- [19] Tong S, Wong NH, Tan E, Jusuf SK. A review on natural ventilation applications through building fac; ade components and ventilation openings in tropical climates. Build Environ 2019;166:106418. <https://doi.org/10.1016/j.buildenv.2019.106418>.
- [20] Aflaki A, Mahyuddin N, Al-Cheikh Mahmoud Z, Baharum MR. A review on natural ventilation applications through building façade components and ventilation openings in tropical climates. Energy Build 2015;101:153–62. <https://doi.org/10.1016/j.enbuild.2015.04.033>.
- [21] Chenari B, Dias Carrilho J, Gameiro da Silva M. Towards sustainable, energy-efficient and healthy ventilation strategies in buildings: a review. Renew Sustain Energy Rev 2016;59:1426–47. <https://doi.org/10.1016/j.rser.2016.01.074>.
- [22] Acar U, Kaşka Ö, Tokgoz N. Multi-objective optimization of building envelope components at the preliminary design stage for residential buildings in Turkey. J Build Eng 2021;42:102499. <https://doi.org/10.1016/j.jobe.2021.102499>.
- [23] Al-Tamimi NA, Fadzil SFS. The potential of shading devices for temperature reduction in high-rise residential buildings in the tropics. Procedia Eng 2011;21: 273–82. <https://doi.org/10.1016/j.proeng.2011.11.2015>.
- [24] Evola G, Margani G, Marletta L. Cost-effective design solutions for low-rise residential Net ZEBs in Mediterranean climate. Energy Build 2014;68:7–18. <https://doi.org/10.1016/j.enbuild.2013.09.026>.
- [25] Giovanardi A, Troi R, Sparber W, Baggio P, Darmstadt P, Considerably H. Dynamic simulation of a passive house in different locations in Italy. 2008.
- [26] Hamida A, Alsudairi A, Alshaibani K, Alshamrani O. Parametric study of the impact of building envelope systems on embodied and operational carbon of residential buildings. Int J Build Pathol Adapt 2021. <https://doi.org/10.1108/IJBPA-08-2020-0064>. ahead-of-print.
- [27] Nikolov N. Use of environmental parameters in building envelope design. Greece: Kos; 2012. p. 215–26. <https://doi.org/10.2495/ARCI20201>.
- [28] Ochoa CE, Capeluto IG. Strategic decision-making for intelligent buildings: comparative impact of passive design strategies and active features in a hot climate. Build Environ 2008;43:1829–39.
- [29] Sarihi S, Mehdizadeh Saradj F, Faizi M. A critical review of façade retrofit measures for minimizing heating and cooling demand in existing buildings. Sustain Cities Soc 2021;64:102525. <https://doi.org/10.1016/j.scs.2020.102525>.
- [30] Singh MC, Garg SN. Energy rating of different glazings for Indian climates. Energy 2009;34:1986. <https://doi.org/10.1016/j.energy.2009.08.013>. –92.
- [31] Tong S, Wen J, Wong NH, Tan E. Impact of façade design on indoor air temperatures and cooling loads in residential buildings in the tropical climate. Energy Build 2021;243:110972. <https://doi.org/10.1016/j.enbuild.2021.110972>.
- [32] Wong NH, Li S. A study of the effectiveness of passive climate control in naturally ventilated residential buildings in Singapore. Build Environ - BLDG Env 2007;42: 1395–405. <https://doi.org/10.1016/j.buildenv.2005.11.032>.
- [33] Verbeke S, Audenaert A. Thermal inertia in buildings: a review of impacts across climate and building use. Renew Sustain Energy Rev 2018;82:2300–18. <https://doi.org/10.1016/j.rser.2017.08.083>.
- [34] Jain AS, Saikia P, Rakshit D. Thermal energy performance of an academic building with sustainable probing and optimization with evolutionary algorithm. Therm Sci Eng Prog 2020;17:100374. <https://doi.org/10.1016/j.tsep.2019.100374>.
- [35] Kim H, Clayton MJ. A multi-objective optimization approach for climate-adaptive building envelope design using parametric behavior maps. Build Environ 2020; 185:107292. <https://doi.org/10.1016/j.buildenv.2020.107292>.
- [36] Li DHW, Yang L, Lam JC. Zero energy buildings and sustainable development implications – a review. Energy 2013;54:1–10. <https://doi.org/10.1016/j.energy.2013.01.070>.
- [37] Queiroz N, Dantas N, Nome C, Vaz C. Designing a Building envelope using parametric and algorithmic processes. 2015. p. 797–801. <https://doi.org/10.5151/despro-sigradi2015-sp90284>.
- [38] Sen R, Bhattacharya SP, Chattopadhyay S. Are low-income mass housing envelopes energy efficient and comfortable? A multi-objective evaluation in warm-humid climate. Energy Build 2021;245:111055. <https://doi.org/10.1016/j.enbuild.2021.111055>.
- [39] Wong I, Baldwin AN. Investigating the potential of applying vertical green walls to high-rise residential buildings for energy-saving in sub-tropical region. Build Environ 2016;97:34–9. <https://doi.org/10.1016/j.buildenv.2015.11.028>.
- [40] Camporeale PE, Mercader-Moyano P. Towards nearly zero energy buildings: shape optimization of typical housing typologies in Ibero-American temperate climate cities from a holistic perspective. Sol Energy 2019;193:738–65. <https://doi.org/10.1016/j.solener.2019.09.091>.
- [41] Ciardiello A, Rosso F, Dell’Omo J, Ciano V, Ferrero M, Salata F. Multi-objective approach to the optimization of shape and envelope in building energy design. Appl Energy 2020;280:115984. <https://doi.org/10.1016/j.apenergy.2020.115984>.
- [42] Giouri ED, Tenpierik M, Turrin M. Zero energy potential of a high-rise office building in a Mediterranean climate: using multi-objective optimization to understand the impact of design decisions towards zero-energy high-rise buildings. Energy Build 2020;209:109666. <https://doi.org/10.1016/j.enbuild.2019.109666>.
- [43] Jin J-T, Jeong J-W. Optimization of a free-form building shape to minimize external thermal load using genetic algorithm. Energy Build 2014;85:473–82. <https://doi.org/10.1016/j.enbuild.2014.09.080>.
- [44] Maksoud A, Mushtaha E, Al-Sadoon Z, Sahall H, Toutou A. Design of Islamic parametric elevation for interior, enclosed corridors to optimize daylighting and solar radiation exposure in a desert climate: a case study of the University of Sharjah. UAE. Buildings 2022;12:161. <https://doi.org/10.3390/buildings12020161>.
- [45] Premrov M, Žegarac Leskovar V, Mihalić K. Influence of the building shape on the energy performance of timber-glass buildings in different climatic conditions. Energy 2016;108:201–11. <https://doi.org/10.1016/j.energy.2015.05.027>.
- [46] Devgan S, Jain AK, Bhattacharjee B. Predetermined overall thermal transfer value coefficients for Composite, Hot-Dry and Warm-Humid climates. Energy Build 2010;42:1841–61.
- [47] Hong T, Kim J, Lee J, Koo C, Park HS. Assessment of seasonal energy efficiency strategies of a double skin façade in a monsoon climate region. Energies 2013;6: 4352–76. <https://doi.org/10.3390/en6094352>.
- [48] Mirrahimi S, Mohamed MF, Haw LC, Ibrahim NLN, Yusoff WFM, Aflaki A. The effect of building envelope on the thermal comfort and energy saving for high-rise buildings in hot-humid climate. Renew Sustain Energy Rev 2016;53:1508–19. <https://doi.org/10.1016/j.rser.2015.09.055>.
- [49] Zilberberg E, Trapper P, Meir IA, Isaac S. The impact of thermal mass and insulation of building structure on energy efficiency. Energy Build 2021;241: 110954. <https://doi.org/10.1016/j.enbuild.2021.110954>.
- [50] Jannat N, Hussien A, Abdullah B, Cotgrave A. A comparative simulation study of the thermal performances of the building envelope wall materials in the tropics. Sustainability 2020;12:4892. <https://doi.org/10.3390/su12124892>.
- [51] Lee CY, Kaneko S, Sharifi A. Effects of building types and materials on household electricity consumption in Indonesia. Sustain Cities Soc 2020;54:101999. <https://doi.org/10.1016/j.scs.2019.101999>.
- [52] Refat KH, Sajjad RN. Prospect of achieving net-zero energy building with semi-transparent photovoltaics: a device to system level perspective. Appl Energy 2020;279:115790. <https://doi.org/10.1016/j.apenergy.2020.115790>.
- [53] Sadeghifan AN, Zahraee SM, Meynagh MM, Kiani I. Combined use of design of experiment and dynamic building simulation in assessment of energy efficiency in

- tropical residential buildings. *Energy Build* 2015;86:525–33. <https://doi.org/10.1016/j.enbuild.2014.10.052>.
- [54] Singh MK, Mahapatra S, Atreya SK. Solar passive features in vernacular architecture of North-East India. *Sol Energy* 2011;85:2011–22.
- [55] Tang R, Meir I, Wu T. Thermal performance of non air-conditioned buildings with vaulted roofs in comparison with flat roofs. *Build Environ* 2006;41:268–76. <https://doi.org/10.1016/j.buildenv.2005.01.008>.
- [56] Widera B. Comparative analysis of user comfort and thermal performance of six types of vernacular dwellings as the first step towards climate resilient, sustainable and bioclimatic architecture in western sub-Saharan Africa. *Renew Sustain Energy Rev* 2021;140:110736. <https://doi.org/10.1016/j.rser.2021.110736>.
- [57] Oraopoulos A, Howard B. On the accuracy of urban building energy modelling. *Renew Sustain Energy Rev* 2022;158:111976. <https://doi.org/10.1016/j.rser.2021.111976>.
- [58] Ascione F, Bianco N, Iovane T, Mastellone M, Mauro GM. The evolution of building energy retrofit via double-skin and responsive façades: a review. *Sol Energy* 2021;224:703–17. <https://doi.org/10.1016/j.solener.2021.06.035>.
- [59] Hashempour N, Taherkhani R, Mahdikhani M. Energy performance optimization of existing buildings: a literature review. *Sustain Cities Soc* 2020;54:101967. <https://doi.org/10.1016/j.scs.2019.101967>.
- [60] Kheiri F. A review on optimization methods applied in energy-efficient building geometry and envelope design. *Renew Sustain Energy Rev* 2018;92:897–920. <https://doi.org/10.1016/j.rser.2018.04.080>.
- [61] Sadini SB, Madala S, Boehm RF. Passive building energy savings: a review of building envelope components. *Renew Sustain Energy Rev* 2011;15:3617–31. <https://doi.org/10.1016/j.rser.2011.07.014>.
- [62] Deb C, Schlueter A. Review of data-driven energy modelling techniques for building retrofit. *Renew Sustain Energy Rev* 2021;144:110990. <https://doi.org/10.1016/j.rser.2021.110990>.
- [63] Pacheco R, Ordóñez J, Martínez G. Energy efficient design of building: a review. *Renew Sustain Energy Rev* 2012;16:3559–73. <https://doi.org/10.1016/j.rser.2012.03.045>.
- [64] Feng W, Zhang Q, Ji H, Wang R, Zhou N, Ye Q, et al. A review of net zero energy buildings in hot and humid climates: experience learned from 34 case study buildings. *Renew Sustain Energy Rev* 2019;114:109303. <https://doi.org/10.1016/j.rser.2019.109303>.
- [65] Friess WA, Rakhshan K. A review of passive envelope measures for improved building energy efficiency in the UAE. *Renew Sustain Energy Rev* 2017;72:485–96. <https://doi.org/10.1016/j.rser.2017.01.026>.
- [66] Ma Z, Wang S. Building energy research in Hong Kong: a review. *Renew Sustain Energy Rev* 2009;13:1870–83. <https://doi.org/10.1016/j.rser.2009.01.006>.
- [67] Zhang H, Yang D, Tam VVY, Tao Y, Zhang G, Setunge S, et al. A critical review of combined natural ventilation techniques in sustainable buildings. *Renew Sustain Energy Rev* 2021;141:110795. <https://doi.org/10.1016/j.rser.2021.110795>.
- [68] Kirmintat A, Koyunbaba BK, Chatzikonstantinou I, Sariyildiz S. Review of simulation modeling for shading devices in buildings. *Renew Sustain Energy Rev* 2016;53:23–49. <https://doi.org/10.1016/j.rser.2015.08.020>.
- [69] Gupta N, Tiwari GN. Review of passive heating/cooling systems of buildings. *Energy Sci Eng* 2016;4:305–33. <https://doi.org/10.1002/ese3.129>.
- [70] Arumugam P, Ramalingam V, Vellaichamy P. Effective PCM, insulation, natural and/or night ventilation techniques to enhance the thermal performance of buildings located in various climates – a review. *Energy Build* 2022;258:111840. <https://doi.org/10.1016/j.enbuild.2022.111840>.
- [71] Bimaganbetova M, Memon SA, Sheriyev A. Performance evaluation of phase change materials suitable for cities representing the whole tropical savanna climate region. *Renew Energy* 2020;148:402–16. <https://doi.org/10.1016/j.renene.2019.10.046>.
- [72] Verma A, Gupta V, Nihar K, Jana A, Jain RK, Deb C. Tropical climates and the interplay between IEQ and energy consumption in buildings: a review. *Build Environ* 2023;242:110551. <https://doi.org/10.1016/j.buildenv.2023.110551>.
- [73] Chang J-H. Thermal comfort and climatic design in the tropics: an historical critique. *J Archit* 2016;21:1171–202. <https://doi.org/10.1080/13602365.2016.1255907>.
- [74] Rodriguez CM, D'Alessandro M. Indoor thermal comfort review: the tropics as the next frontier. *Urban Clim* 2019;29:100488. <https://doi.org/10.1016/j.uclim.2019.100488>.
- [75] Fang Y, Cho S. Design optimization of building geometry and fenestration for daylighting and energy performance. *Sol Energy* 2019;191:7–18. <https://doi.org/10.1016/j.solener.2019.08.039>.
- [76] Siew CC, Che-Ani AI, Tawil NM, Abdullah NAG, Mohd-Tahir M. Classification of natural ventilation strategies in optimizing energy consumption in Malaysian office buildings. *Procedia Eng* 2011;20:363–71. <https://doi.org/10.1016/j.proeng.2011.11.178>.
- [77] Gamero-Salinas J, Monge-Barrio A, Kishnani N, López-Fidalgo J, Sánchez-Ostiz A. Passive cooling design strategies as adaptation measures for lowering the indoor overheating risk in tropical climates. *Energy Build* 2021;252:111417. <https://doi.org/10.1016/j.enbuild.2021.111417>.
- [78] Nedhal A-T, Syed Fadzil S, Harun W. The effects of orientation, ventilation, and varied WWR on the thermal performance of residential rooms in the tropics. *J Sustain Dev* 2011;4:142–9. <https://doi.org/10.5539/jsd.v4n2p142>.
- [79] Lei J, Kumarasamy K, Zingre KT, Yang J, Wan MP, Yang E-H. Cool colored coating and phase change materials as complementary cooling strategies for building cooling load reduction in tropics. *Appl Energy* 2017;190:57–63. <https://doi.org/10.1016/j.apenergy.2016.12.114>.
- [80] Lee C, Hong T, Lee G, Jeong J. Life-cycle cost analysis on glass type of high-rise buildings for increasing energy efficiency and reducing co2 emissions in Korea. *J Construct Eng Manag* 2012;138:897–904. [https://doi.org/10.1061/\(ASCE\)CO.1943-7862.0000502](https://doi.org/10.1061/(ASCE)CO.1943-7862.0000502).
- [81] Sarmiento Hugo. New paradigms in tropical limnology: the importance of the microbial food web. *Hydrobiologia* 2012;686:1–14. <https://doi.org/10.1007/s10750-012-1011-6>.
- [82] Feeley K, Stroud J. Where on earth are the “tropics”? 2018;vol. 10:1–7. <https://doi.org/10.21425/F5101-238649>.
- [83] Peel MC, Finlayson BL, McMahon TA. Updated world map of the Köppen-Geiger climate classification. *Hydrol Earth Syst Sci* 2007;11:1633–44. <https://doi.org/10.5194/hess-11-1633-2007>.
- [84] Deb C, Lee SE. Determining key variables influencing energy consumption in office buildings through cluster analysis of pre- and post-retrofit building data. *Energy Build* 2018;159:228–45. <https://doi.org/10.1016/j.enbuild.2017.11.007>.
- [85] Garde F, Adelaar L, Boyer H, Rat C. Implementation and experimental survey of passive design specifications used in new low-cost housing under tropical climates. *Energy Build* 2004;36:353–66. <https://doi.org/10.1016/j.enbuild.2004.01.045>.
- [86] Deb C, Frei M, Schlueter A. Identifying temporal properties of building components and indoor environment for building performance assessment. *Build Environ* 2020;168:106506. <https://doi.org/10.1016/j.buildenv.2019.106506>.
- [87] Saikia P, Pancholi M, Sood D, Rakshit D. Dynamic optimization of multi-retrofit building envelope for enhanced energy performance with a case study in hot Indian climate. *Energy* 2020;197:117263. <https://doi.org/10.1016/j.energy.2020.117263>.
- [88] Cicelsky A, Meir IA. Parametric analysis of environmentally responsive strategies for building envelopes specific for hot hyperarid regions. *Sustain Cities Soc* 2014;13:279–302.
- [89] Kumar A, Suman BM. Experimental evaluation of insulation materials for walls and roofs and their impact on indoor thermal comfort under composite climate. *Build Environ* 2013;59:635–43. <https://doi.org/10.1016/j.buildenv.2012.09.023>.
- [90] Koenigsberger OH. Manual of tropical housing and building. Longman London; 1974.
- [91] Neya I, Yamegueu D, Coulibaly Y, Messan A, Ouedraogo ALS-N. Impact of insulation and wall thickness in compressed earth buildings in hot and dry tropical regions. *J Build Eng* 2021;33:101612. <https://doi.org/10.1016/j.jobe.2020.101612>.
- [92] Pinterić M. Building physics. 2nd, illustrated ed. Cham, Switzerland: Springer International Publishing; 2021.
- [93] Gupta V, Deb C. Energy retrofit analysis for an educational building in Mumbai. *Sustain Futur* 2022;4:100096. <https://doi.org/10.1016/j.sfr.2022.100096>.
- [94] Deb C, Gelder LV, Spiekman M, Pandraud G, Jack R, Fittion R. Measuring the heat transfer coefficient (HTC) in buildings: a stakeholder's survey. *Renew Sustain Energy Rev* 2021;144:111008. <https://doi.org/10.1016/j.rser.2021.111008>.
- [95] Huang H, Zhou Y, Huang R, Wu H, Sun Y, Huang G, et al. Optimum insulation thicknesses and energy conservation of building thermal insulation materials in Chinese zone of humid subtropical climate. *Sustain Cities Soc* 2020;52:101840. <https://doi.org/10.1016/j.scs.2019.101840>.
- [96] Friess WA, Rakhshan K, Hendawi TA, Tazerzadeh S. Wall insulation measures for residential villas in Dubai: a case study in energy efficiency. *Energy Build* 2012;44:26–32. <https://doi.org/10.1016/j.enbuild.2011.10.005>.
- [97] Singh MK, Mahapatra S, Tech M. Design optimization of vernacular building in warm and humid climate of North-East India, vol. 9; 2014.
- [98] Drissi Lamrhari EH, Benhamou B. Thermal behavior and energy saving analysis of a flat with different energy efficiency measures in six climates. *Build Simulat* 2018;2018:1–12. <https://doi.org/10.1007/s12273-018-0467-3>.
- [99] Zune M, Tubelo R, Rodrigues L, Gillott M. Improving building thermal performance through an integration of Passivhaus envelope and shading in a tropical climate. *Energy Build* 2021;253:111521. <https://doi.org/10.1016/j.enbuild.2021.111521>.
- [100] Masoso OT, Grobler LJ. A new and innovative look at anti-insulation behaviour in building energy consumption. *Energy Build* 2008;40:1889–94. <https://doi.org/10.1016/j.enbuild.2008.04.013>.
- [101] Lam JC, Wan KKW, Liu D, Tsang CL. Multiple regression models for energy use in air-conditioned office buildings in different climates. *Energy Convers Manag* 2010;51:2692–7. <https://doi.org/10.1016/j.enconman.2010.06.004>.
- [102] Lee JW, Jung HJ, Park JY, Lee JB, Yoon Y. Optimization of building window system in Asian regions by analyzing solar heat gain and daylighting elements. *Renew Energy* 2013;50:522–31.
- [103] Machado MV, Roche PML. Materials and appropriate design strategies for buildings in hot climates. 1999. p. 357–62.
- [104] Theodosiou T, Laskos K, Bikas D. Assessing cooling energy performance of windows for office buildings in the Mediterranean zone. *Energy Build*; 2012.
- [105] Afshari A, Nikolopoulou C, Martin M. Life-cycle analysis of building retrofits at the urban scale—a case study in United Arab Emirates. *Sustainability* 2014;6:453–73. <https://doi.org/10.3390/su6010453>.
- [106] Radhi H. Evaluating the potential impact of global warming on the UAE residential buildings – a contribution to reduce the CO2 emissions. *Build Environ* 2009;44:2451–62. <https://doi.org/10.1016/j.buildenv.2009.04.006>.
- [107] Sierra-Pérez J, Rodríguez-Soria B, Boschmonart-Rives J, Gabarrell X. Integrated life cycle assessment and thermodynamic simulation of a public building's envelope renovation: conventional vs. Passivhaus proposal. *Appl Energy* 2018;212:1510–21. <https://doi.org/10.1016/j.apenergy.2017.12.101>.

- [108] Elghamry R, Hassan H. Impact of window parameters on the building envelope on the thermal comfort, energy consumption and cost and environment. *Int J Vent* 2020;19:233–59. <https://doi.org/10.1080/14733315.2019.1665784>.
- [109] Ayyad TM, Fadeyi MO. Effects of building facade materials on building energy consumption in the tropics. *10th Int Conf Healthy Build* 2012;3:2163–8.
- [110] Altaf M, Hill F. Identifying optimum glazing property for conserving energy in hot semi-arid climate regions. *J Green Build* 2021;16:91–101. <https://doi.org/10.3992/jgb.16.1.91>.
- [111] Cuce E, Riffat SB. Aerogel-assisted support pillars for thermal performance enhancement of vacuum glazing: a CFD research for a commercial product. *Arabian J Sci Eng* 2015;40:2233–8. <https://doi.org/10.1007/s13369-015-1727-5>.
- [112] Lollini R, Barozzi B, Fasano G, Meroni I, Zinzi M. Optimisation of opaque components of the building envelope. Energy, economic and environmental issues. *Build Environ* 2006;1001–13.
- [113] Ahn B-L, Kim J-H, Jang C-Y, Leigh S-B, Jeong H. Window retrofit strategy for energy saving in existing residences with different thermal characteristics and window sizes. *Build Serv Eng Res Technol* 2015;37. <https://doi.org/10.1177/0143624415595904>.
- [114] Ourghi R, Alanzi A, Krarti M. A simplified analysis method to predict the impact of shape on annual energy use for office buildings. *Energy Convers Manag* 2007;48:300–5. <https://doi.org/10.1016/j.enconman.2006.04.011>.
- [115] Al-Saadi S, Al-Jabri K. Energy-efficient envelope design for residential buildings: a case study in Oman. 2017. <https://doi.org/10.1109/SCSP.2017.7973853>.
- [116] Zhao B, Qi L, Yang T. Simulation and analysis of the energy consumption for public buildings in different climate regions of China. *Procedia Eng* 2017;205:2940–7. <https://doi.org/10.1016/j.proeng.2017.10.110>.
- [117] Alaidroos A, Krarti M. Optimal design of residential building envelope systems in the Kingdom of Saudi Arabia. *Energy Build* 2015;86. <https://doi.org/10.1016/j.enbuild.2014.09.083>.
- [118] Smith KM, Holroyd P. Chapter 7 - heat. In: Smith KM, Holroyd P, editors. *Eng. Princ. Electr. Tech. Pergamon*; 1968. p. 134–55. <https://doi.org/10.1016/B978-0-08-012985-3.50012-1>.
- [119] Dili AS, Naseer MA, Zacharia Varghese T. Passive control methods of Kerala traditional architecture for a comfortable indoor environment: comparative investigation during various periods of rainy season. *Build Environ* 2010;45:2218–30. <https://doi.org/10.1016/j.buildenv.2010.04.002>.
- [120] Alayed E, Bensaid D, O'Hegarty R, Kinnane O. Thermal mass impact on energy consumption for buildings in hot climates: a novel finite element modelling study comparing building constructions for arid climates in Saudi Arabia. *Energy Build* 2022;271:112324. <https://doi.org/10.1016/j.enbuild.2022.112324>.
- [121] Kuczyński T, Staszczuk A. Experimental study of the influence of thermal mass on thermal comfort and cooling energy demand in residential buildings. *Energy* 2020;195:116984. <https://doi.org/10.1016/j.energy.2020.116984>.
- [122] Chen Y, Xu P, Chen Z, Wang H, Sha H, Ji Y, et al. Experimental investigation of demand response potential of buildings: combined passive thermal mass and active storage. *Appl Energy* 2020;280:115956. <https://doi.org/10.1016/j.apenergy.2020.115956>.
- [123] Olsthoorn D, Haghighat F, Moreau A, Lacroix G. Abilities and limitations of thermal mass activation for thermal comfort, peak shifting and shaving: a review. *Build Environ* 2017;118:113–27. <https://doi.org/10.1016/j.buildenv.2017.03.029>.
- [124] Rodrigues E, Fernandes MS, Gaspar AR, Gomes Á, Costa JJ. Thermal transmittance effect on energy consumption of Mediterranean buildings with different thermal mass. *Appl Energy* 2019;252:113437. <https://doi.org/10.1016/j.apenergy.2019.113437>.
- [125] Dornelles KA, Roriz M. Thermal inertia, comfort and energy consumption in buildings: a case study in São Paulo state - Brazil. *Montreal: Canada*; 2003.
- [126] Stazi F, Tomassoni E, Bonfigli C, Di Perna C. Energy, comfort and environmental assessment of different building envelope techniques in a Mediterranean climate with a hot dry summer. *Appl Energy* 2014;134:176–96. <https://doi.org/10.1016/j.apenergy.2014.08.023>.
- [127] Bagasi AA, Calauti JK. Experimental field study of the integration of passive and evaporative cooling techniques with Mashrabiya in hot climates. *Energy Build* 2020;225:110325. <https://doi.org/10.1016/j.enbuild.2020.110325>.
- [128] Shaviv E. The influence of the orientation of the main solar glazing on the total energy consumption of a building. *Sol Energy* 1981;26:453–4.
- [129] Ogoli DM. Predicting indoor temperatures in closed buildings with high thermal mass. *Energy Build* 2003;35:851–62. [https://doi.org/10.1016/S0378-7788\(02\)00246-3](https://doi.org/10.1016/S0378-7788(02)00246-3).
- [130] Di Perna C, Stazi F, Casalena AU, D'Orazio M. Influence of the internal inertia of the building envelope on summertime comfort in buildings with high internal heat loads. *Energy Build* 2011;43:200–6. <https://doi.org/10.1016/j.enbuild.2010.09.007>.
- [131] Leo Samuel DG, Dharmasastha K, Shiva Nagendra SM, Maiya MP. Thermal comfort in traditional buildings composed of local and modern construction materials. *Int J Sustain Built Environ* 2017;6:463–75. <https://doi.org/10.1016/j.ijbs.2017.08.001>.
- [132] Lecce F, Salvadori G, Asdrubali F, Gori P. Passive thermal behaviour of buildings: performance of external multi-layered walls and influence of internal walls. *Appl Energy* 2018;225:1078–89. <https://doi.org/10.1016/j.apenergy.2018.05.090>.
- [133] Ren Z, Chen D. Modelling study of the impact of thermal comfort criteria on housing energy use in Australia. *Appl Energy* 2018;210:152–66. <https://doi.org/10.1016/j.apenergy.2017.10.110>.
- [134] Chiraratananon S, Hien VD. Thermal performance and cost effectiveness of massive walls under Thai climate. *Energy Build* 2011;43:1655–62. <https://doi.org/10.1016/j.enbuild.2011.03.010>.
- [135] Ralegaonkar RV, Gupta R. Review of intelligent building construction: a passive solar architecture approach. *Renew Sustain Energy Rev* 2010;14:2238–42. <https://doi.org/10.1016/j.rser.2010.04.016>.
- [136] Li Y, Yao J, Li R, Zhang Z, Zhang J. Thermal and energy performance of a steel-bamboo composite wall structure. *Energy Build* 2017;156:225–37. <https://doi.org/10.1016/j.enbuild.2017.09.083>.
- [137] Kossecka E, Kosny J. Influence of insulation configuration on heating and cooling loads in a continuously used building. *Energy Build* 2002;34:321–31. [https://doi.org/10.1016/S0378-7788\(01\)00121-9](https://doi.org/10.1016/S0378-7788(01)00121-9).
- [138] Zhu L, Hurt R, Correia D, Boehm R. Detailed energy saving performance analyses on thermal mass walls demonstrated in a zero energy house. *Energy Build* 2009;41:303–10. <https://doi.org/10.1016/j.enbuild.2008.10.003>.
- [139] Ferrari S. Building envelope and heat capacity: re-discovering the thermal mass for winter energy saving. Greece: Crete Island; 2007.
- [140] Stazi F, Vegliò A, Di Perna C, Munafò P. Experimental comparison between 3 different traditional wall constructions and dynamic simulations to identify optimal thermal insulation strategies. *Energy Build* 2013;60:429–41. <https://doi.org/10.1016/j.enbuild.2013.01.032>.
- [141] Reilly A, Kinnane O. The impact of thermal mass on building energy consumption. *Appl Energy* 2017;198:108–21. <https://doi.org/10.1016/j.apenergy.2017.04.024>.
- [142] Kumar S, Singh MK, Mathur A, Mathur S, Mathur J. Thermal performance and comfort potential estimation in low-rise high thermal mass naturally ventilated office buildings in India: an experimental study. *J Build Eng* 2018;20:569–84. <https://doi.org/10.1016/j.jobe.2018.09.003>.
- [143] Shaviv E, Yezioro A, Capeluto IG. Thermal mass and night ventilation as passive cooling design strategy. *Renew Energy* 2001;24:445–52. [https://doi.org/10.1016/S0960-1481\(01\)00027-1](https://doi.org/10.1016/S0960-1481(01)00027-1).
- [144] Kuczyński T, Staszczuk A, Gortych M, Stryjski R. Effect of thermal mass, night ventilation and window shading on summer thermal comfort of buildings in a temperate climate. *Build Environ* 2021;204:108126. <https://doi.org/10.1016/j.buildenv.2021.108126>.
- [145] Alonso C, Martín-Consuegra F, Oteiza I, Asensio E, Pérez G, Martínez I, et al. Effect of façade surface finish on building energy rehabilitation. *Sol Energy* 2017;146:470–83. <https://doi.org/10.1016/j.solener.2017.03.009>.
- [146] Alonso C, Oteiza I, García-Navarro J, Martín-Consuegra F. Energy consumption to cool and heat experimental modules for the energy refurbishment of façades. Three case studies in Madrid. *Energy Build* 2016;126:252–62. <https://doi.org/10.1016/j.enbuild.2016.04.034>.
- [147] Kolokotroni M, Gowreesunker BL, Giridharan R. Cool roof technology in London: an experimental and modelling study. *Energy Build* 2013;67:658–67. <https://doi.org/10.1016/j.enbuild.2011.07.011>.
- [148] Ascione F, Bellia L, Mazzei P, Minichiello F. Solar gain and building envelope: the surface factor. *Build Res Inf* 2010;38:187–205. <https://doi.org/10.1080/09613210903529118>.
- [149] Garg V, Kotharkar R, Sathaye J, Rallapalli H, Kulkarni N, Reddy N, et al. Assessment of the impact of cool roofs in rural buildings in India. *Energy Build* 2016;114:156–63. <https://doi.org/10.1016/j.enbuild.2015.06.043>.
- [150] Saber HH. Experimental characterization of reflective coating material for cool roofs in hot, humid and dusty climate. *Energy Build* 2021;242:110993. <https://doi.org/10.1016/j.enbuild.2021.110993>.
- [151] Yu J, Yang C, Tian L. Low-energy envelope design of residential building in hot summer and cold winter zone in China. *Energy Build* 2008;40:1536–46. <https://doi.org/10.1016/j.enbuild.2008.02.020>.
- [152] Pisello AL, Castaldo VL, Rosso F, Piselli C, Ferrero M, Cotana F. Traditional and innovative materials for energy efficiency in buildings. *Key Eng Mater* 2016;678:14–34. <https://doi.org/10.4028/www.scientific.net/KEM.678.14>.
- [153] Malz S, Krenkel W, Steffens O. Infrared reflective wall paint in buildings: energy saving potentials and thermal comfort. *Energy Build* 2020;224:110212. <https://doi.org/10.1016/j.enbuild.2020.110212>.
- [154] Medved S. Building physics: heat, ventilation, moisture, light, sound, fire, and urban microclimate. Springer Nature; 2021.
- [155] Shi Z, Zhang X. Analyzing the effect of the longwave emissivity and solar reflectance of building envelopes on energy-saving in buildings in various climates. *Sol Energy* 2011;85:28–37. <https://doi.org/10.1016/j.solener.2010.11.009>.
- [156] Wong WH, Jusuf SK. Urban heat island and mitigation strategies at city and building level. *Scopus* 2013. <https://doi.org/10.2174/9781608054718113010004>. <https://scholarbank.nus.edu.sg/handle/10635/114120>. [Accessed 21 March 2022].
- [157] Seifhashemi M, Capra BR, Müller W, Bell J. The potential for cool roofs to improve the energy efficiency of single storey warehouse-type retail buildings in Australia: a simulation case study. *Energy Build* 2018;158:1393–403. <https://doi.org/10.1016/j.enbuild.2017.11.034>.
- [158] Pisello AL, Castaldo VL, Piselli C, Fabiani C, Cotana F. Thermal performance of coupled cool roof and cool façade: experimental monitoring and analytical optimization procedure. *Energy Build* 2017;157:35–52. <https://doi.org/10.1016/j.enbuild.2017.04.054>.
- [159] Kachkouch S, Ait-Nouh F, Benhamou B, Limam K. Experimental assessment of thermal performance of three passive cooling techniques for roofs in a semi-arid climate. *Energy Build* 2018;164:153–64. <https://doi.org/10.1016/j.enbuild.2018.01.008>.

- [160] Synnefa A, Santamouris M, Akbari H. Estimating the effect of using cool coatings on energy loads and thermal comfort in residential buildings in various climatic conditions. *Energy Build* 2007;39:1167–74. <https://doi.org/10.1016/j.enbuild.2007.01.004>.
- [161] Bhatia A, Mathur J, Garg V. Calibrated simulation for estimating energy savings by the use of cool roof in five Indian climatic zones. *J Renew Sustain Energy* 2011;3:023108. <https://doi.org/10.1063/1.3582768>.
- [162] Xu T, Sathaye J, Akbari H, Garg V, Tetali S. Quantifying the direct benefits of cool roofs in an urban setting: reduced cooling energy use and lowered greenhouse gas emissions. *Build Environ* 2012;48:1–6. <https://doi.org/10.1016/j.buildenv.2011.08.011>.
- [163] Romeo C, Zinzi M. Impact of a cool roof application on the energy and comfort performance in an existing non-residential building. A Sicilian case study. *Energy Build* 2013;67:647–57. <https://doi.org/10.1016/j.enbuild.2011.07.023>.
- [164] Dimoudi A, Androustopoulos A, Lykoudis S. Summer performance of a ventilated roof component. *Energy Build* 2006;38:610–7. <https://doi.org/10.1016/j.enbuild.2005.09.006>.
- [165] Fathy H. *Natural energy and vernacular architecture*. 1986.
- [166] Givoni B. *Climate considerations in building and urban design*. John Wiley & Sons; 1998.
- [167] Nahar NM, Sharma P, Purohit MM. Performance of different passive techniques for cooling of buildings in arid regions. *Build Environ* 2003;38:109–16. [https://doi.org/10.1016/S0360-1323\(02\)00029-X](https://doi.org/10.1016/S0360-1323(02)00029-X).
- [168] Suehrcke H, Peterson EL, Selby N. Effect of roof solar reflectance on the building heat gain in a hot climate. *Energy Build* 2008;40:2224–35. <https://doi.org/10.1016/j.enbuild.2008.06.015>.
- [169] Nahar NM, Sharma P, Purohit MM. Studies on solar passive cooling techniques for arid areas. *Energy Convers Manag* 1999;40:89–95. [https://doi.org/10.1016/S0196-8904\(98\)00039-9](https://doi.org/10.1016/S0196-8904(98)00039-9).
- [170] Santamouris M, Synnefa A, Karlessi T. Using advanced cool materials in the urban built environment to mitigate heat islands and improve thermal comfort conditions. *Sol Energy* 2011;85:3085–102. <https://doi.org/10.1016/j.solener.2010.12.023>.
- [171] Pathirana S, Rodrigo A, Halwatura R. Effect of building shape, orientation, window to wall ratios and zones on energy efficiency and thermal comfort of naturally ventilated houses in tropical climate. *Int J Energy Environ Eng* 2019;10:107–20. <https://doi.org/10.1007/s40095-018-0295-3>.
- [172] Foroughi R, Mostavi E, Asadi S. Determining the optimum geometrical design parameters of windows in commercial buildings: comparison between humid subtropical and humid continental climate zones in the United States. *J Architect Eng* 2018;24:04018026. [https://doi.org/10.1061/\(ASCE\)AE.1943-5568.0000329](https://doi.org/10.1061/(ASCE)AE.1943-5568.0000329).
- [173] Anand P, Deb C, Alur R. A simplified tool for building layout design based on thermal comfort simulations. *Front Archit Res* 2017;6:218–30. <https://doi.org/10.1016/j.foar.2017.03.001>.
- [174] Coleridge T, Huh R. Performance analysis of external shading devices: a case study of office building typology in Cape Town. South Africa; 2017.
- [175] El-Darwish I, Gomaa M. Retrofitting strategy for building envelopes to achieve energy efficiency. *Alex Eng J* 2017;56:579–89. <https://doi.org/10.1016/j.aej.2017.05.011>.
- [176] Liu S, Kwok YT, Lau KK-L, Chan PW, Ng E. Investigating the energy saving potential of applying shading panels on opaque façades: a case study for residential buildings in Hong Kong. *Energy Build* 2019;193:78–91. <https://doi.org/10.1016/j.enbuild.2019.03.044>.
- [177] Ip K, Lam M, Miller A. Shading performance of a vertical deciduous climbing plant canopy. *Build Environ* 2010;45:81–8. <https://doi.org/10.1016/j.buildenv.2009.05.003>.
- [178] Wong NH, Kwang Tan AY, Chen Y, Sekar K, Tan PY, Chan D, et al. Thermal evaluation of vertical greenery systems for building walls. *Build Environ* 2010;45:663–72. <https://doi.org/10.1016/j.buildenv.2009.08.005>.
- [179] Alexandri E, Jones P. Temperature decreases in an urban canyon due to green walls and green roofs in diverse climates. *Build Environ* 2008;43:480–93. <https://doi.org/10.1016/j.buildenv.2006.10.055>.
- [180] Campbell GS, Norman John M. *An Introduction to environmental biophysics*. New York: Springer-Verlag New York Inc.; 1998.
- [181] Anwar M, Rasul MG, Khan MMK. Performance analysis of rooftop greenery systems in Australian subtropical climate. *Energy Rep* 2020;6:50–6. <https://doi.org/10.1016/j.egyr.2019.08.017>.
- [182] Stec WJ, van Paassen AHC, Maziarz A. Modelling the double skin façade with plants. *Energy Build* 2005;37:419–27. <https://doi.org/10.1016/j.enbuild.2004.08.008>.
- [183] Al-Qahtani LAH, Elgizawi LSE. Building envelope and energy saving case study: a residential building in Al-Riyadh, Saudi Arabia. *Int J Low Carbon Technol* 2020;15:555–64. <https://doi.org/10.1093/ijlct/ctaa024>.
- [184] Barbosa S, Ip K, Southall R. Thermal comfort in naturally ventilated buildings with double skin façade under tropical climate conditions: the influence of key design parameters. *Energy Build* 2015;109:397–406. <https://doi.org/10.1016/j.enbuild.2015.10.029>.
- [185] Duarte C, Raftery P. Development of whole-building energy models for detailed energy insights of a large office building with green certification rating in Singapore. *Energy Technol* 2017;6. <https://doi.org/10.1002/ente.201700564>.
- [186] Chi DA, Moreno D, Navarro J. Design optimisation of perforated solar façades in order to balance daylighting with thermal performance. *Build Environ* 2017;125:383–400. <https://doi.org/10.1016/j.buildenv.2017.09.007>.
- [187] Chel A, Tiwari G. Thermal performance and embodied energy analysis of a passive house – case study of vault roof mud-house in India. *Appl Energy* 2009;86:1956–69. <https://doi.org/10.1016/j.apenergy.2008.12.033>.
- [188] Elasfour AS, Maraqa R, Tabbalat R. Shading control by neighbouring buildings: application to buildings in Amman, Jordan. *Int J Refrig* 1991;14:112–6. [https://doi.org/10.1016/0140-7007\(91\)90083-S](https://doi.org/10.1016/0140-7007(91)90083-S).
- [189] Wang W, Zmeureanu R, Rivard H. Applying multi-objective genetic algorithms in green building design optimization. *Build Environ* 2005;40:1512–25. <https://doi.org/10.1016/j.buildenv.2004.11.017>.
- [190] Qi F, Wang Y. A new calculation method for shape coefficient of residential building using Google Earth. *Energy Build* 2014;76:72–80. <https://doi.org/10.1016/j.enbuild.2014.02.058>.
- [191] Catalina T, Iordache V. IEQ assessment on schools in the design stage. *Build Environ* 2012;49:129–40. <https://doi.org/10.1016/j.buildenv.2011.09.014>.
- [192] Oral G, Yilmaz AZ. The limit U values for building envelope related to building form in temperate and cold climatic zones. *Build Environ* 2002;37:1173–80. [https://doi.org/10.1016/S0360-1323\(01\)00102-0](https://doi.org/10.1016/S0360-1323(01)00102-0).
- [193] Depecker P, Menezes C, Virgone J, Lepers S. Design of buildings shape and energetic consumption. *Build Environ* 2001;36:627–35. [https://doi.org/10.1016/S0360-1323\(00\)00044-5](https://doi.org/10.1016/S0360-1323(00)00044-5).
- [194] Florides G, Tassou S, Kalogirou S, Wrobel L. Measures used to lower building energy consumption and their cost effectiveness. *Appl Energy* 2002;73. [https://doi.org/10.1016/S0306-2619\(02\)00119-8](https://doi.org/10.1016/S0306-2619(02)00119-8).
- [195] Amraoui K, Sriti L, Di Turi S, Ruggiero F, Kailoul A. Exploring building's envelope thermal behavior of the neo-vernacular residential architecture in a hot and dry climate region of Algeria. *Build Simulat* 2021;14:1567–84. <https://doi.org/10.1007/s12273-021-0764-0>.
- [196] Ling CS, Ahmad MH, Ossen DR. The effect of geometric shape and building orientation on minimising solar insolation on high-rise buildings in hot humid climate, vol. 12; 2007.
- [197] Adamski M. Optimization of the form of a building on an oval base. *Build Environ - BLDG Env* 2007;42:1632–43. <https://doi.org/10.1016/j.buildenv.2006.02.004>.
- [198] Olgyay V, Olgyay A, Lyndon D, Olgyay VW, Reynolds J, Yeang K. Design with climate: bioclimatic approach to architectural regionalism - new, expanded edition. REV-Revised. Princeton University Press; 2015. <https://doi.org/10.2307/j.ctvc77kqb>.
- [199] Jin J-T, Jeong J-W. Thermal characteristic prediction models for a free-form building in various climate zones. *Energy* 2013;50:468–76. <https://doi.org/10.1016/j.energy.2012.11.011>.
- [200] Westermann P, Evins R. Surrogate modelling for sustainable building design – a review. *Energy Build* 2019;198:170–86. <https://doi.org/10.1016/j.enbuild.2019.05.057>.
- [201] Sharma P, Rakshit D. Quantitative assessment of orientation impact on heat gain profile of naturally cooled buildings in India. *Adv Build Energy Res* 2017;11:208–26. <https://doi.org/10.1080/17512549.2016.1215261>.
- [202] Al-Tamimi NAM. Impact of building envelope modifications on the thermal performance of glazed high-rise residential buildings in the tropics. 2011. p. 46.
- [203] Gao CF, Lee WL. Evaluating the influence of openings configuration on natural ventilation performance of residential units in Hong Kong. *Build Environ* 2011;46:961–9. <https://doi.org/10.1016/j.buildenv.2010.10.029>.
- [204] Rached E, Anber M. Energy retrofitting strategies for office buildings in hot arid climate. *Int J Low Carbon Technol* 2022;17:506–12. <https://doi.org/10.1093/ijlct/ctac031>.
- [205] Kharseh M, Al-Khawaja M. Retrofitting measures for reducing buildings cooling requirements in cooling-dominated environment: residential house. *Appl Therm Eng* 2016;98:352–6. <https://doi.org/10.1016/j.applthermaleng.2015.12.063>.
- [206] Pourghorban A, Kari BM, Asodeh H. Holistic survey of reflective insulation systems (RISs) in vertical applications in building envelopes under various climatic conditions. *Energy* 2022;242:122959. <https://doi.org/10.1016/j.energy.2021.122959>.
- [207] Hwang R-L, Chen W-A. Identifying relative importance of solar design determinants on office building façade for cooling loads and thermal comfort in hot-humid climates. *Build Environ* 2022;226:109684. <https://doi.org/10.1016/j.buildenv.2022.109684>.
- [208] Albatayneh A, Tayara T, Jaradat M, Al-Omary M, Hindiye M, Alterman D, et al. Optimum building design variables in a warm Saharan mediterranean climate zone. *Int J Photoenergy* 2021;2021:e6672260. <https://doi.org/10.1155/2021/6672260>.
- [209] Lakhdari K, Sriti L, Painter B. Parametric optimization of daylight, thermal and energy performance of middle school classrooms, case of hot and dry regions. *Build Environ* 2021;204:108173. <https://doi.org/10.1016/j.buildenv.2021.108173>.
- [210] Yu J, Yang C, Tian L. Low-energy envelope design of residential building in hot summer and cold winter zone in China. *Energy Build* 2008;40:1536–46. <https://doi.org/10.1016/j.enbuild.2008.02.020>.
- [211] Ariff A, Ahmad S, Hussin M. Green envelope as an architectural strategy for energy efficiency in a library building. *MATEC Web Conf* 2019;266:01004. <https://doi.org/10.1051/mateconf/201926601004>.
- [212] William MA, Suárez-López MJ, Soutullo S, Hanafy AA. Building envelopes toward energy-efficient buildings: a balanced multi-approach decision making. *Int J Energy Res* 2021;45:21096. <https://doi.org/10.1002/er.7166>.
- [213] Alhuwayil WK, Abdul Mujeeb M, Algarny AMM. Impact of external shading strategy on energy performance of multi-story hotel building in hot-humid climate. *Energy* 2019;169:1166–74. <https://doi.org/10.1016/j.energy.2018.12.069>.

- [214] Chan ALS. Energy and environmental performance of building façades integrated with phase change material in subtropical Hong Kong. *Energy Build* 2011;43: 2947–55. <https://doi.org/10.1016/j.enbuild.2011.07.021>.
- [215] Gamaleldine M, Corvacho H. Compliance with building energy code for the residential sector in Egyptian hot-arid climate: potential impact, difficulties, and further improvements. *Sustainability* 2022;14:3936. <https://doi.org/10.3390/su14073936>.
- [216] Jones JS. Research methods datasets Part 2 - learn to use the Eta coefficient test in R with data from the NIOSH quality of worklife survey (2014). SAGE Publications, Ltd.; 2019.
- [217] IBM, Cramér's V, Cramér's V. <https://prod.ibmdocs-production-dal-6099123ce774e592a519d7c33db8265e-0000.us-south.containers.appdomain.cloud/docs/en/cognos-analytics/11.1.0?topic=terms-crams-v>. [Accessed 24 November 2022].
- [218] Chen B, Liu Q, Chen H, Wang L, Deng T, Zhang L, et al. Multiobjective optimization of building energy consumption based on BIM-DB and LSSVM-NSGA-II. *J Clean Prod* 2021;294:126153. <https://doi.org/10.1016/j.jclepro.2021.126153>.
- [219] Wang Y, Wei C. Design optimization of office building envelope based on quantum genetic algorithm for energy conservation. *J Build Eng* 2021;35:102048. <https://doi.org/10.1016/j.jobe.2020.102048>.
- [220] Bano F, Sehgal V. Evaluation of energy-efficient design strategies: comparison of the thermal performance of energy-efficient office buildings in composite climate, India. *Sol Energy* 2018;176:506–19. <https://doi.org/10.1016/j.solener.2018.10.057>.
- [221] Gong X, Akashi Y, Sumiyoshi D. Optimization of passive design measures for residential buildings in different Chinese areas. *Build Environ* 2012;58:46–57. <https://doi.org/10.1016/j.buildenv.2012.06.014>.
- [222] Zhou Y, Zheng S. Climate adaptive optimal design of an aerogel glazing system with the integration of a heuristic teaching-learning-based algorithm in machine learning-based optimization. *Renew Energy* 2020;153:375–91. <https://doi.org/10.1016/j.renene.2020.01.133>.
- [223] Chow D, Sharples S. The feasibility of retrofitting existing office buildings to combat energy consumption due to future climate change in three key regions of China. China: Suzhou; 2015. p. 1–9.
- [224] Yokeswaran R, Siva Chandran S, Sathish kumar V, Loganathan M, Veluchamy B. Influence of different insulation materials for effective cooling performance. *Mater Today Proc* 2022. <https://doi.org/10.1016/j.matpr.2022.07.417>.
- [225] Kumar G, Thakur B, De S. Energy performance of typical large residential apartments in Kolkata: implementing new energy conservation building codes of India. *Clean Technol Environ Policy* 2021;23:1251–71. <https://doi.org/10.1007/s10098-020-02022-7>.
- [226] Jayanthi RV, Bhattacharjee B, Scartezzini JL. Role of insulation in energy consumption in commercial and office buildings. 2015. p. 759–66.
- [227] Ali Al-Arja O, Awadallah TS. Energy consumption optimization in schools sector in Jordan. *Architect Sci Rev* 2016;59:400–12. <https://doi.org/10.1080/00038628.2015.1012637>.
- [228] Singh R, Lazarus LJ, Kishore VVN. Uncertainty and sensitivity analyses of energy and visual performances of office building with external Venetian blind shading in hot-dry climate. *Appl Energy* 2016;184:155–70. <https://doi.org/10.1016/j.apenergy.2016.10.007>.
- [229] Putra IDGA, Nimiya H, Sopaheluwakan A, Kubota T, Lee HS, Pradana RP, et al. Development of climate zones for passive cooling techniques in the hot and humid climate of Indonesia. *Build Environ* 2022;226. <https://doi.org/10.1016/j.buildenv.2022.109698>.
- [230] Tenorio R. Dual mode cooling house in the warm humid tropics. *Sol Energy* 2002; 73:43–57. [https://doi.org/10.1016/S0038-092X\(02\)00002-6](https://doi.org/10.1016/S0038-092X(02)00002-6).
- [231] Safarova S, Halawa E, Campbell A, Law L, Hoof J. Pathways for optimal provision of thermal comfort and sustainability of residential housing in hot and humid tropics of Australia – a critical review. *Indoor Built Environ* 2017;27: 1420326X1770180. <https://doi.org/10.1177/1420326X17701805>.
- [232] Gokarakonda S, van Treeck C, Rawal R. Influence of building design and control parameters on the potential of mixed-mode buildings in India. *Build Environ* 2019;148:157–72. <https://doi.org/10.1016/j.buildenv.2018.10.043>.
- [233] Chen R, Tsay Y-S. An integrated sensitivity analysis method for energy and comfort performance of an office building along the Chinese coastline. *Buildings* 2021;11:371. <https://doi.org/10.3390/buildings11080371>.
- [234] Sekhar SC. Higher space temperatures and better thermal comfort — a tropical analysis. *Energy Build* 1995;23:63–70. [https://doi.org/10.1016/0378-7788\(95\)00932-N](https://doi.org/10.1016/0378-7788(95)00932-N).
- [235] Chou SK, Wong YW, Chang WL, Yap C. Efficient energy performance of large commercial buildings in tropical climates. *Energy Convers Manag* 1994;35: 751–63. [https://doi.org/10.1016/0196-8904\(94\)90104-X](https://doi.org/10.1016/0196-8904(94)90104-X).
- [236] Mangkuto RA, Rohmah M, Asri AD. Design optimisation for window size, orientation, and wall reflectance with regard to various daylight metrics and lighting energy demand: a case study of buildings in the tropics. *Appl Energy* 2016;164:211–9. <https://doi.org/10.1016/j.apenergy.2015.11.046>.
- [237] Wang JS, Demartino C, Xiao Y, Li YY. Thermal insulation performance of bamboo- and wood-based shear walls in light-frame buildings. *Energy Build* 2018; 168:167–79. <https://doi.org/10.1016/j.enbuild.2018.03.017>.
- [238] Mathur U, Damle R. Impact of air infiltration rate on the thermal transmittance value of building envelope. *J Build Eng* 2021;40. <https://doi.org/10.1016/j.jobe.2021.102302>.
- [239] Hong T, Kim J, Lee M. A multi-objective optimization model for determining the building design and occupant behaviors based on energy, economic, and environmental performance. *Energy* 2019;174:823–34. <https://doi.org/10.1016/j.energy.2019.02.035>.
- [240] Radwan AF, Hanafy AA, Elhelw M, El-Sayed AE-HA. Retrofitting of existing buildings to achieve better energy-efficiency in commercial building case study: hospital in Egypt. *Alex Eng J* 2016;55:3061–71. <https://doi.org/10.1016/j.aej.2016.08.005>.
- [241] Raji B, Tenpierik MJ, Van Den Dobbelsteen A. Early-stage design considerations for the energy-efficiency of high-rise office buildings. *Sustainability* 2017;9:623. <https://doi.org/10.3390/su9040623>.
- [242] Toutou A, Fikry M, Mohamed W. The parametric based optimization framework daylighting and energy performance in residential buildings in hot arid zone. *Alex Eng J* 2018;57:3595–608. <https://doi.org/10.1016/j.aej.2018.04.006>.
- [243] Lee S, Kang J-S, Choi H-J, Choi G-S. Study on SHGC calculation and measurement of window installed with shading device. *Int J Thermophys* 2020;41:106. <https://doi.org/10.1007/s10765-020-02684-x>.
- [244] Koo C, Park S, Hong T, Park HS. An estimation model for the heating and cooling demand of a residential building with a different envelope design using the finite element method. *Appl Energy* 2014;115:205–15. <https://doi.org/10.1016/j.apenergy.2013.11.014>.
- [245] Delgarm N, Sajadi B, Kowsary F, Delgarm S. Multi-objective optimization of the building energy performance: a simulation-based approach by means of particle swarm optimization (PSO). *Appl Energy* 2016;170:293–303. <https://doi.org/10.1016/j.apenergy.2016.02.141>.
- [246] Azari R, Garshasbi S, Amini P, Rashed-Ali H, Mohammadi Y. Multi-objective optimization of building envelope design for life cycle environmental performance. *Energy Build* 2016;126:524–34. <https://doi.org/10.1016/j.enbuild.2016.05.054>.
- [247] Ghabra N, Rodrigues L, Oldfield P. The impact of the building envelope on the energy efficiency of residential tall buildings in Saudi Arabia. *Int J Low Carbon Technol* 2017;12:411–9. <https://doi.org/10.1093/ijlct/ctx005>.
- [248] Yao J. Energy uncertainty of manual solar shades for different window-to-wall ratios. *J Asian Architect Build Eng* 2019;18:575–85. <https://doi.org/10.1080/13467581.2019.1696205>.
- [249] Manu S, Brager G, Rawal R, Geronazzo A, Kumar D. Performance evaluation of climate responsive buildings in India - case studies from cooling dominated climate zones. *Build Environ* 2019;148:136–56. <https://doi.org/10.1016/j.buildenv.2018.10.063>.
- [250] Goswami S, Natrajan V. A simulation study to assess the energy efficiency and thermal comfort performance of internal wall assemblies for residential construction in warm and humid climate, vol. 2020; 2020. p. 131–40. November.